Safety Data Sheet

according to Regulation (EU) 2015/830 Date of issue: 7/27/2016 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Tool Box Buddy Aerosol

Product code : . 10392, 40392

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Lucas Oil Products, Inc 302 North Sheridan Street 92880-2067 Corona, California - USA T (951) 270-0154 - F (951) 270-1902 GHewgill@lucasoil.com - www.LucasOil.com

1.4. Emergency telephone number

Emergency number : (951) 493-1149 (951) 847-5949 7:00A.M. to 5:00P.M. Monday thru Friday

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Sensitisation — Skin, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :









Signal word (CLP) : Danger

Hazardous ingredients : Distillates (petroleum), hydrotreated light; Sulfonic acid, petroleum, calcium salts, overbased

Hazard statements (CLP) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

7/27/2016 EN (English) SDS Ref.: LUK1607005 1/11

Safety Data Sheet

according to Regulation (EU) 2015/830

smoking

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing vapours, spray

P264 - Wash hands thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves, protective clothing

P301+P310 - If swallowed: Immediately call a poison center or doctor

P302+P352 - IF ON SKIN: Wash with plenty of water

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P312 - Call a poison center or doctor if you feel unwell

P321 - Specific treatment (see First aid measures on this label)

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P391 - Collect spillage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

PBT: not yet assessed vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light	(CAS No) 64742-47-8 (EC no) 265-149-8 (EC index no) 649-422-00-2	40 – 70	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane (Note U)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	10 – 15	Flam. Gas 1, H220
n-Butane (Note C)(Note U)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	5 – 10	Flam. Gas 1, H220
Sulfonic acid, petroleum, calcium salts, overbased	(CAS No) 68783-96-0 (EC no) 272-213-9	3 – 7	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 4, H413

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Get immediate medical advice/attention. If medical advice is needed, have product container or label at hand. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

First-aid measures after inhalation

: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

7/27/2016 EN (English) SDS Ref.: LUK1607005 2/11

Safety Data Sheet

according to Regulation (EU) 2015/830

First-aid measures after skin contact : Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse

mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Shortness of breath. Danger of serious damage to health by prolonged exposure through

inhalation. Harmful if inhaled. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. Rapid evaporation of the liquid may

cause frostbite.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. May damage lungs if swallowed and aspirated.

Risk of aspiration pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Flammable vapours may accumulate in the container. Heating

may cause a fire or explosion. Heavier than air, vapours may travel long distances along

ground, ignite and flash back to source.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries. Contains gas under pressure; may explode if heated.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area. Fight fire remotely due to the risk of explosion. Keep away from ignition

sources.

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Eliminate all ignition sources if safe to do so.

Exercise caution when fighting any chemical fire. In case of fire: stop leak if safe to do so. Use

water spray or fog for cooling exposed containers.

Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. EN469.

Other information : Do not pierce or burn, even after use.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges. Do not breathe aerosol.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Use personal protective equipment as required. Refer to section 8.2.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required. Refer to section 8.2.

Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

7/27/2016 EN (English) SDS Ref.: LUK1607005 3/11

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardo

: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use. Flammable vapours heavier than air/can accumulate. Vapour could travel

to source of ignition and flash back.

Precautions for safe handling : Do not spray on an open flame or other ignition source. Use only outdoors or in a well-

ventilated area. Avoid contact with skin, eyes and clothing. Do not breathe vapours. Do not

pierce or burn, even after use.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the

workplace. Wash contaminated clothing before reuse. Work in a well-ventilated area.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep

container tightly closed.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in a dry, cool area.

7.3. Specific end use(s)

Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated light (64742-47-8)			
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	600 mg/m³	
Propane (74-98-6)	Propane (74-98-6)		
Denmark	Grænseværdie (kortvarig) (mg/m³)	3600 mg/m³	
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm	
n-Butane (106-97-8)			
Austria	MAK (mg/m³)	1900 mg/m³	
Austria	MAK (ppm)	800 ppm	
Austria	MAK Short time value (mg/m³)	3800 mg/m³ max. 3x60 min./Schicht	
Austria	MAK Short time value (ppm)	1600 ppm max. 3x60 min./Schicht	
Belgium	Limit value (ppm)	1000 ppm	
Denmark	Grænseværdie (langvarig) (mg/m³)	1200 mg/m³	
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm	
Denmark	Grænseværdie (kortvarig) (mg/m³)	2400 mg/m³	
Denmark	Grænseværdie (kortvarig) (ppm)	1000 ppm	
Finland	HTP-arvo (8h) (mg/m³)	1900 mg/m³	
Finland	HTP-arvo (8h) (ppm)	800 ppm	
Finland	HTP-arvo (15 min)	2400 mg/m³	
Finland	HTP-arvo (15 min) (ppm)	1000 ppm	
France	VME (mg/m³)	1900 mg/m³	
France	VME (ppm)	800 ppm	
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	2400 mg/m³	
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm	
Hungary	AK-érték	2350 mg/m³	
Hungary	CK-érték	9400 mg/m³	
Ireland	OEL (8 hours ref) (ppm)	1000 ppm	
Poland	NDS (mg/m³)	1900 mg/m³	
Poland	NDSCh (mg/m³)	3000 mg/m ³	
Slovakia	NPHV (priemerná) (mg/m³)	2400 mg/m ³	
Slovakia	NPHV (priemerná) (ppm)	1000 ppm	

7/27/2016 EN (English) SDS Ref.: LUK1607005 4/11

Safety Data Sheet

according to Regulation (EU) 2015/830

n-Butane (106-97-8)		
Slovakia	Upozornenie (SK)	(Dokázaný karcinogén pre ludí, Pravdepodobný mutagén)
Spain	VLA-ED (mg/m³)	1935 mg/m³
Spain	VLA-ED (ppm)	800 ppm
United Kingdom	WEL TWA (mg/m³)	1450 mg/m³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m³)	1810 mg/m³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	(Carc, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Norway	Grenseverdier (AN) (mg/m³)	600 mg/m³
Norway	Grenseverdier (AN) (ppm)	250 ppm
Switzerland	VME (mg/m³)	1900 mg/m³
Switzerland	VME (ppm)	800 ppm
Australia	TWA (mg/m³)	1450 mg/m³
Australia	TWA (ppm)	600 ppm
Australia	STEL (mg/m³)	1810 mg/m³
Australia	STEL (ppm)	750 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains should be available

in the immediate vicinity of any potential exposure.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves. EN 374

Eye protection:

Chemical goggles or safety glasses. EN166

Respiratory protection:

Decomposition temperature

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. EN 136/140

Environmental exposure controls : Prevent leakage or spillage.

Other information : Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol.
Colour : amber.

Odour : petroleum. Solvent. Odour threshold : No data available pН : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available : No data available Freezing point Boiling point : No data available : < 37.8 °C Flash point Auto-ignition temperature : No data available

Flammability (solid, gas) : Heat of combustion,-11.5 kJ/g,Extremely flammable aerosol

: No data available

Vapour pressure : No data available Relative vapour density at 20 °C : No data available

Relative density : 0.8285
Solubility : Negligible.
Log Pow : No data available
Viscosity, kinematic : 1.5 cSt @ 100 °C

7/27/2016 EN (English) SDS Ref.: LUK1607005 5/11

Safety Data Sheet

according to Regulation (EU) 2015/830

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 25 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating may cause an explosion.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). Hydrocarbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	2.344 mg/l/4h
Distillates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5.28 mg/l/4h

Sulfonic acid, petroleum, calcium salts, overbased (68783-96-0)	
LD50 oral rat	> 20000 mg/kg
LD50 dermal rabbit	> 20000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated :

exposure)

: Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Tool Box Buddy Aerosol	
Viscosity, kinematic	1.5 mm ² /s @ 100 °C

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated light (64742-47-8)	
LC50 fish 1	> 1 mg/l 96 h
NOEC chronic fish	> 0.01 <= 0.1 mg/l
NOEC chronic crustacea	> 0.01 <= 0.1 mg/l

7/27/2016 EN (English) SDS Ref.: LUK1607005 6/11

Safety Data Sheet

according to Regulation (EU) 2015/830

Sulfonic acid, petroleum, calcium salts, overbased (68783-96-0)	
LC50 fish 1	40 mg/l 96 h Pimephales promelas
EC50 Daphnia 1	> 1000 mg/l 48 h
EC50 72h algae (1)	> 1000 mg/l 96 h Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Tool Box Buddy Aerosol	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Tool Box Buddy Aerosol	
Bioaccumulative potential Not established.	
Distillates (petroleum), hydrotreated light (64742-47-8)	
Log Kow	2.1 - 5
Bioaccumulative potential	Bioaccumulative potential.

12.4. Mobility in soil

Tool Box Buddy Aerosol	
Ecology - soil	No additional information available.

12.5. Results of PBT and vPvB assessment

Tool Box Buddy Aerosol	
PBT: not yet assessed	
vPvB: not yet assessed	

12.6. Other adverse effects

Additional information : No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in

accordance with local/national regulations. Do not pierce or burn, even after use.

Additional information : Flammable vapours may accumulate in the container.

Ecology - waste materials : Hazardous waste due to toxicity.

European List of Waste (LoW) code : For disposal within the EC, the appropriate code according to the European Waste Catalogue

(EWC) should be used

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

 UN-No. (ADR)
 : 1950

 UN-No. (IMDG)
 : 1950

 UN-No. (IATA)
 : 1950

 UN-No. (ADN)
 : 1950

 UN-No. (RID)
 : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : AEROSOLS, flammable

Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

Transport document description (IATA) : UN 1950 AEROSOLS, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS

Transport document description (ADN) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS Transport document description (RID) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1

7/27/2016 EN (English) SDS Ref.: LUK1607005 7/11

Safety Data Sheet

according to Regulation (EU) 2015/830

Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes

Other information : No supplementary information available

7/27/2016 EN (English) SDS Ref.: LUK1607005 8/11

Safety Data Sheet

according to Regulation (EU) 2015/830

Special precautions for user 14.6.

- Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02 : PP87, RR6, L2 Special packing provisions (ADR)

Mixed packing provisions (ADR) : MP9 Transport category (ADR) : 2 Special provisions for carriage - Packages : V14

(ADR)

Special provisions for carriage - Loading,

unloading and handling (ADR)

Tunnel restriction code (ADR)

: CV9, CV12

: S2

: D

Special provisions for carriage - Operation

(ADR)

- Transport by sea

: 63, 190, 277, 327, 344, 959 Special provisions (IMDG)

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1. SW22 Segregation (IMDG) : SG69

- Air transport

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

- Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L Excepted quantities (ADN) : E0 Equipment required (ADN) : PP, EX, A : VE01, VE04 Ventilation (ADN)

Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID)

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP02 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9 Transport category (RID) : 2

7/27/2016 EN (English) SDS Ref.: LUK1607005 9/11

Safety Data Sheet

according to Regulation (EU) 2015/830

Special provisions for carriage - Packages

Special provisions for carriage - Loading,

unloading and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

Transport in bulk according to Annex II of MARPOL and the IBC Code 14.7.

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

: W14

: CW9, CW12

15.1.1. **EU-Regulations**

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 25 %

National regulations 15.1.2.

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS,

Annex 4)

12th Ordinance Implementing the Federal

Immission Control Act - 12.BlmSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

: Distillates (petroleum), hydrotreated light, Sulfonic acid, petroleum, calcium salts, overbased are SZW-lijst van kankerverwekkende stoffen

: Distillates (petroleum), hydrotreated light, Sulfonic acid, petroleum, calcium salts, overbased are SZW-lijst van mutagene stoffen

listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: None of the components are listed

Denmark

: Class II-1 Class for fire hazard Store unit : 5 liter

: R10 <H222;H229;H304;H315;H317;H319;H332;H336;H411>; Emergency management Classification remarks

guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation Young people below the age of 18 years are not allowed to use the product

The requirements from the Danish Working Environment Authorities regarding work with

carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population
STEL: Short Term Exposure Limits
TWA: Time Weighted Average

7/27/2016 SDS Ref.: LUK1607005 10/11 EN (English)

Safety Data Sheet

according to Regulation (EU) 2015/830

Data sources

: European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	Expert judgment
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS prepared by: The Redstone Group, LLC.

6077 Frantz Rd. Suite 206 Dublin, Ohio, USA 43016

614.923.7472 www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

7/27/2016 EN (English) SDS Ref.: LUK1607005 11/11