



Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878
Date d'émission: 11/03/2022 Version: 1.0

RUBRIQUE 1: Identification de la substance/du mélange et de la société/l'entreprise

1.1. Identificateur de produit

Forme du produit : Mélange
Nom commercial : Lucas Synthetic SAE 5W-40 European Motor Oil
Lucas SAE 30 Break-In Oil
Lucas Semi-Synthetic SAE 10W-40 European Motor Oil
Lucas Synthetic SAE 5W-30 European Motor Oil
Lucas Semi-Synthetic SAE 5W-30 European Motor Oil
Lucas SAE 85W-140 Heavy Duty Gear Oil
Lucas SAE 80W-90 Heavy Duty Gear Oil
Lucas Synthetic SAE 15W-40 Magnum CJ-4
Lucas SAE 20W-50 Break-In Oil
Lucas Power Steering Fluid
Lucas Synthetic SAE 10W-60 European Motor Oil
Lucas Semi-Synthetic SAE 15W-40 European Motor Oil
Lucas Synthetic SAE 10W-30 European Motor Oil
Lucas Power Steering Fluid with Conditioners
L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil
L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil
L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil
L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil
Lucas SAE 75W-140 Synthetic Gear Oil
Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil
Lucas SAE 75W-90 Synthetic Gear Oil
Lucas Synthetic SAE 10W-40 Outboard Engine Oil
Lucas SAE 15W-40 Magnum CI-4/SM
Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30
Anti-Squawk/Anti-Shudder Trans & Diff Additive
Lucas Synthetic SAE 20W-50 European Motor Oil

Code du produit :

1.2. Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées

1.2.1. Utilisations identifiées pertinentes

Destiné au grand public
Catégorie d'usage principal : Utilisation industrielle, Utilisation professionnelle, Utilisation par les consommateurs
Utilisation de la substance/mélange : Lubrifiant.

1.2.2. Utilisations déconseillées

Restrictions d'emploi : Pas d'informations complémentaires

1.3. Renseignements concernant le fournisseur de la fiche de données de sécurité

Fournisseur
Lucas Oil Products UK Ltd
Unit 4 Cunliffe Drive
Llangefni Industrial Estate

Fournisseur
Lucas Oil Products Europe Ltd
Block 3 Harcourt Centre
Harcourt Road

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

LL77 7JA Llangefni
Anglesey - UK
T 01248 723 666

Info@LucasOil.co.uk - www.lucasoil.co.uk

Dublin 2

Ireland

T +44 344 225 5400

info@lucasoil.eu.com www.lucasoil.eu.com

1.4. Numéro d'appel d'urgence

Numéro d'urgence

: ChemTel

1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)

+1-813-248-0585 (International)

Pays	Organisme/Société	Adresse	Numéro d'urgence	Commentaire
France	ORFILA		+33 1 45 42 59 59	Ce numéro fournit les coordonnées de tous les centres antipoison Français. Ces centres de poison et de toxicovigilance fournissent une assistance médicale gratuite (hors frais d'appel), 24 heures sur 24, 7 jours sur 7.

RUBRIQUE 2: Identification des dangers

2.1. Classification de la substance ou du mélange

Classification selon le règlement (CE) N° 1272/2008

Dangereux pour le milieu aquatique – Danger chronique, catégorie 3 H412

Texte intégral des phrases H et EUH: voir section 16

Effets néfastes physicochimiques, pour la santé humaine et pour l'environnement

Pas d'informations complémentaires disponibles

2.2. Éléments d'étiquetage

Etiquetage selon le règlement (CE) N° 1272/2008 [CLP]

Mention d'avertissement (CLP)

: -

Mentions de danger (CLP)

: H412 - Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Conseils de prudence (CLP)

: P101 - En cas de consultation d'un médecin, garder à disposition le récipient ou l'étiquette.

P102 - Tenir hors de portée des enfants.

P103 - Lire attentivement et bien respecter toutes les instructions.

P273 - Éviter le rejet dans l'environnement.

P501 - Éliminer le contenu/récipient dans un centre de collecte de déchets dangereux ou spéciaux, conformément à la réglementation locale, régionale, nationale et/ou internationale.

Toxicité aiguë inconnue (CLP: Classification, étiquetage, emballage.) - FDS

: le mélange contient 8,1% de composants dont la toxicité aiguë est inconnue (Oral)

le mélange contient 8,6% de composants dont la toxicité aiguë est inconnue (Cutané)

le mélange contient 8,6% de composants dont la toxicité aiguë est inconnue (Inhalation (Poussières/brouillards))

Dangers pour l'environnement aquatique inconnus (CLP)

: Contient 9,23 % de composants dont la toxicité pour le milieu aquatique est inconnue

Fermeture de sécurité pour enfants

: Non applicable

Indications de danger détectables au toucher

: Non applicable

2.3. Autres dangers

vPvB: pas encore évalué

Ne contient aucune substance PBT/vPvB $\geq 0,1$ % évaluée conformément à l'annexe XIII de REACH

Composant	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Composant	
	Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
tetrapropenylphenol (74499-35-7)	PBT: non pertinent – pas d'enregistrement requis vPvB: non pertinent – pas d'enregistrement requis Summary: tetrapropenylphenol is considered to clearly meet the T criterion, and is likely to meet the P and vP criteria with a reasonable degree of confidence. It does not meet the TGD B or vB criteria, and so is not considered a PBT substance according to the EU criteria.
Phenol, dodecyl-, branched (121158-58-5)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Phenol, dodecyl-, branched (121158-58-5)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Toluene (108-88-3)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Benzene (71-43-2)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
ethylenediamine (107-15-3)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII

Le mélange contient une ou plusieurs substances inscrites sur la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnu comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission

Composant	
tetrapropenylphenol(74499-35-7)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission
Phenol, dodecyl-, branched(121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission
Phenol, dodecyl-, branched (121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Composant	
ethylenediamine(107-15-3)	La substance n'apparaît pas dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou n'est pas reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission

RUBRIQUE 3: Composition/informations sur les composants

3.1. Substances

Non applicable

3.2. Mélanges

Nom	Identificateur de produit	%	Classification selon le règlement (CE) N° 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) substance possédant des valeurs limites d'exposition professionnelle communautaires (Note L)	N° CAS: 64742-54-7 N° CE: 265-157-1 N° Index: 649-467-00-8 N° REACH: 01-2119484627-0018	10 - 90	Carc. Non classé
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (Note L)	N° CAS: 64742-55-8 N° CE: 265-158-7 N° Index: 649-468-00-3	0 - 60	Carc. Non classé Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%) (Note L)	N° CAS: 72623-86-0 N° CE: 276-737-9 N° Index: 649-482-00-X	0 - 30	Carc. Non classé Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	N° CAS: 68037-01-4 N° CE: 212-819-2	0 - 20	Asp. Tox. 1, H304
sulfurized isobutylene	N° CAS: 68511-50-2 N° CE: 270-943-2	0 - 12	Aquatic Chronic 4, H413
Distillates (petroleum), hydrotreated light naphthenic (DMSO <3%) (Note L)	N° CAS: 64742-53-6 N° CE: 265-156-6 N° Index: 649-466-00-2	0 - 10	Carc. Non classé Asp. Tox. 1, H304
Mineral oil (DMSO <3%)	N° CAS: mixture	≤ 7,5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO <3%)	N° CAS: 64742-65-0 N° CE: 265-169-7 N° Index: 649-474-00-6	0 - 7.5	Acute Tox. 4 (par inhalation : poussières, brouillard), H332 Asp. Tox. 1, H304
Zinc bis[O(6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)-	N° CAS: 93819-94-4 N° CE: 298-577-9	< 6,25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Isobutene-butene polymer	N° CAS: 9003-29-6 N° CE: 500-004-7	0 - 5,15	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Antimony, tris(dipentylcarbamodithioato-S,S')-	N° CAS: 15890-25-2 N° CE: 240-028-2	0 - 5	Acute Tox. 4 (par voie orale), H302 Acute Tox. 4 (par voie cutanée), H312 Aquatic Chronic 2, H411
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (Note L)	N° CAS: 64742-65-0 N° CE: 265-169-7 N° Index: 649-474-00-6	0 - 4,5	Carc. Non classé Asp. Tox. 1, H304

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Nom	Identificateur de produit	%	Classification selon le règlement (CE) N° 1272/2008 [CLP]
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	N° CAS: 68442-22-8 N° CE: 270-478-5	0 – 2,85	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	N° CAS: 2215-35-2 N° CE: 218-679-9	0 – 2,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	N° CAS: 84605-29-8 N° CE: 283-392-8	0 - <2	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	N° CAS: 134758-95-5	0 – 1,75	Eye Irrit. 2, H319
Polybutene	N° CAS: 9003-29-6 N° CE: 500-004-7	≤ 1,5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
bis(nonylphenyl)amine	N° CAS: 36878-20-3 N° CE: 253-249-4	≤ 1,5	Aquatic Chronic 4, H413
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	N° CAS: 36878-20-3 N° CE: 253-249-4	0 – 1,15	Aquatic Chronic 4, H413
Zinc alkyl dithiophosphate	N° CAS: 113706-15-3	0 – 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	N° CAS: 68649-42-3 N° CE: 272-028-3	0 – 0,6	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
2,6-di-tert-butylphenol	N° CAS: 128-39-2 N° CE: 204-884-0	0 - 0.6	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Tricresylphosphate	N° CAS: 1330-78-5 N° CE: 215-548-8	0 - 0.6	Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Amines, C12-14-alkyl, C6-10-alkyl phosphates	N° CAS: 68603-55-4 N° CE: 271-663-3	0 – 0,5	Acute Tox. 4 (par voie orale), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400
Calcium carbonate substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR)	N° CAS: 471-34-1 N° CE: 207-439-9	0 – 0,3	Non classé
Oleylamine	N° CAS: 112-90-3 N° CE: 204-015-5 N° Index: 612-283-00-3	0 - 0.5	Acute Tox. 4 (par voie orale), H302 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Nom	Identificateur de produit	%	Classification selon le règlement (CE) N° 1272/2008 [CLP]
Diphenylamine substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR)	N° CAS: 122-39-4 N° CE: 204-539-4 N° Index: 612-026-00-5	0 – 0,15	Acute Tox. 3 (par voie orale), H301 Acute Tox. 3 (par voie cutanée), H311 Acute Tox. 3 (par inhalation), H331 Acute Tox. 3 (par inhalation : poussières, brouillard), H331 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
tetrapropenylphenol substance de la liste candidate REACH (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP)) substance identified as having endocrine disrupting properties	N° CAS: 74499-35-7 N° CE: 310-154-3 N° Index: 604-092-00-9	0 – 0,15	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Phenol, dodecyl-, branched substance de la liste candidate REACH (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP)) substance identified as having endocrine disrupting properties	N° CAS: 121158-58-5 N° CE: 310-154-3 N° Index: 604-092-00-9	0 – 0,115	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) substance possédant des valeurs limites d'exposition professionnelle communautaires (Note P)	N° CAS: 64742-48-9 N° CE: 265-150-3 N° Index: 649-327-00-6	0 – 0,095	Flam. Liq. 3, H226 Muta. Non classé Carc. Non classé Asp. Tox. 1, H304
Phenol, dodecyl-, branched substance de la liste candidate REACH (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP))	N° CAS: 121158-58-5 N° CE: 310-154-3 N° Index: 604-092-00-9	0 – 0,09	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Toluene substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 108-88-3 N° CE: 203-625-9 N° Index: 601-021-00-3	0 - <0.07	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
1,2,4-triméthylbenzène substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 95-63-6 N° CE: 202-436-9 N° Index: 601-043-00-3	< 0,025	Flam. Liq. 3, H226 Acute Tox. 4 (par inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Nom	Identificateur de produit	%	Classification selon le règlement (CE) N° 1272/2008 [CLP]
Benzene substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires (Note E (obsolète))	N° CAS: 71-43-2 N° CE: 200-753-7 N° Index: 601-020-00-8	< 0,015	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
éthylbenzène substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 100-41-4 N° CE: 202-849-4 N° Index: 601-023-00-4	0 - < 0.02	Flam. Liq. 2, H225 Acute Tox. 4 (par inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
mésitylène; 1,3,5-triméthylbenzène substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 108-67-8 N° CE: 203-604-4 N° Index: 601-025-00-5	< 0,012	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411
1,2,3-Triméthylbenzène substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 526-73-8 N° CE: 208-394-8	< 0,012	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Xylenes substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires (Note C)	N° CAS: 1330-20-7 N° CE: 215-535-7 N° Index: 601-022-00-9	< 0,012	Flam. Liq. 3, H226 Acute Tox. 4 (par voie cutanée), H312 Acute Tox. 4 (par inhalation), H332 Skin Irrit. 2, H315
Naphthalene substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires	N° CAS: 91-20-3 N° CE: 202-049-5 N° Index: 601-052-00-2	< 0,011	Acute Tox. 4 (par voie orale), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
cumene substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR); substance possédant des valeurs limites d'exposition professionnelle communautaires (Note C)	N° CAS: 98-82-8 N° CE: 202-704-5 N° Index: 601-024-00-X	< 0,01	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylenediamine substance de la liste candidate REACH (Ethylenediamine) substance possédant une/des valeurs limites d'exposition professionnelle nationales (FR)	N° CAS: 107-15-3 N° CE: 203-468-6 N° Index: 612-006-00-6	0 - <0.01	Flam. Liq. 3, H226 Acute Tox. 4 (par voie orale), H302 Acute Tox. 4 (par voie cutanée), H312 Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1, H317

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Limites de concentration spécifiques		
Nom	Identificateur de produit	Limites de concentration spécifiques
Zinc bis[O(6-méthylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)-	N° CAS: 93819-94-4 N° CE: 298-577-9	(6,25 ≤C < 100) Skin Irrit. 2, H315 (10 ≤C < 12,5) Eye Irrit. 2, H319 (12,5 ≤C < 100) Eye Dam. 1, H318
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	N° CAS: 68442-22-8 N° CE: 270-478-5	(10 ≤C < 12,5) Eye Irrit. 2, H319 (12,5 ≤C ≤ 100) Eye Dam. 1, H318
Zinc alkyl dithiophosphate	N° CAS: 113706-15-3	(10 ≤C < 12,5) Eye Irrit. 2, H319 (12,5 ≤C < 100) Eye Dam. 1, H318
mésitylène; 1,3,5-triméthylbenzène	N° CAS: 108-67-8 N° CE: 203-604-4 N° Index: 601-025-00-5	(25 ≤C ≤ 100) STOT SE 3, H335

Note C : Certaines substances organiques peuvent être commercialisées soit sous une forme isomérique bien définie, soit sous forme de mélange de plusieurs isomères. Dans ces cas-là, le fournisseur doit préciser sur l'étiquette si la substance est un isomère spécifique ou un mélange d'isomères.

Note E : Les substances ayant des effets spécifiques sur la santé humaine (chapitre 4 de l'annexe VI de la directive 67/548/ CEE) qui sont classées comme cancérogènes, mutagènes et/ou toxiques pour la reproduction dans les catégories 1 ou 2 se voient attribuer la note E lorsqu'elles sont également classées comme très toxiques (T+), toxiques (T) ou nocives (Xn). Pour ces substances, les phrases R20, R21, R22, R23, R24, R25, R26, R27, R28, R39, R68 (nocif), R48 et R65 ainsi que toutes les combinaisons de ces phrases de risque doivent être précédées du terme «également». (obsolète)

Note L : La classification comme cancérogène peut ne pas s'appliquer s'il peut être établi que la substance contient moins de 3 % d'extrait de diméthyl sulfoxyde (DMSO), mesuré selon la méthode IP 346 «Détermination de substances aromatiques polycycliques dans les huiles de base lubrifiantes inutilisées et les coupes pétrolières sans asphaltène — méthode de l'indice de réfraction de l'extraction de diméthyl-sulfoxyde», Institute of Petroleum de Londres. La présente note ne s'applique qu'à certaines substances complexes dérivées du pétrole, visées dans la troisième partie.

Note P: La classification comme cancérogène ou mutagène peut ne pas s'appliquer s'il peut être établi que la substance contient moins de 0,1 % poids/poids de benzène (no Einecs 200-753-7). Si la substance n'est pas classée comme cancérogène ou mutagène, il convient d'appliquer pour le moins les conseils de prudence (P102-)P260-P262-P301 + P310-P331. La présente note ne s'applique qu'à certaines substances complexes dérivées du pétrole, visées dans la partie 3.

Texte intégral des phrases H et EUH: voir section 16

RUBRIQUE 4: Premiers secours

4.1. Description des premiers secours

Premiers soins général	: Ne jamais administrer quelque chose par la bouche à une personne inconsciente.
Premiers soins après inhalation	: Transporter la personne à l'extérieur et la maintenir dans une position où elle peut confortablement respirer.
Premiers soins après contact avec la peau	: Laver avec précaution et abondamment à l'eau et au savon.
Premiers soins après contact oculaire	: En cas de contact, rincer immédiatement les yeux à grande eau.
Premiers soins après ingestion	: NE PAS faire vomir. Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise.

4.2. Principaux symptômes et effets, aigus et différés

Symptômes/effets après inhalation : L'inhalation de vapeurs peut irriter les voies respiratoires.

4.3. Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires

Traitement symptomatique.

RUBRIQUE 5: Mesures de lutte contre l'incendie

5.1. Moyens d'extinction

Moyens d'extinction appropriés	: Dioxyde de carbone. Produit chimique sec. Mousse. Eau pulvérisée.
Agents d'extinction non appropriés	: Ne pas utiliser un fort courant d'eau.

5.2. Dangers particuliers résultant de la substance ou du mélange

Danger d'incendie : La combustion produit des fumées irritantes, toxiques et nocives.

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

5.3. Conseils aux pompiers

- Instructions de lutte contre l'incendie : Empêcher les effluents de la lutte contre le feu de pénétrer dans les égouts ou les cours d'eau. Refroidir les conteneurs exposés par pulvérisation ou brouillard d'eau.
- Protection en cas d'incendie : Porter un appareil respiratoire autonome. Porter des vêtements résistant au feu/aux flammes/ignifuges. EN469.

RUBRIQUE 6: Mesures à prendre en cas de dispersion accidentelle

6.1. Précautions individuelles, équipement de protection et procédures d'urgence

- Mesures générales : Éviter tout contact avec les yeux et la peau et ne pas respirer les vapeurs et brouillards.

6.1.1. Pour les non-secouristes

- Équipement de protection : Reportez-vous à la section 8.2.
- Procédures d'urgence : Eloigner le personnel superflu.

6.1.2. Pour les secouristes

- Équipement de protection : Reportez-vous à la section 8.2.
- Procédures d'urgence : Obturer la fuite si cela peut se faire sans danger. Aérer la zone.

6.2. Précautions pour la protection de l'environnement

Ne pas rejeter à l'égout ou dans l'environnement.

6.3. Méthodes et matériel de confinement et de nettoyage

- Pour la rétention : Contenir la matière déversée en l'endigant ou à l'aide de matières absorbantes de façon à empêcher l'écoulement dans les égouts ou les cours d'eau.
- Procédés de nettoyage : Absorber et / ou contenir le déversement avec une matière inerte et placer dans un récipient approprié.

6.4. Référence à d'autres rubriques

Section 13: informations sur l'élimination. Section 7: la manipulation. Section 8: équipement de protection individuelle.

RUBRIQUE 7: Manipulation et stockage

7.1. Précautions à prendre pour une manipulation sans danger

- Précautions à prendre pour une manipulation sans danger : Éviter tout contact avec les yeux et la peau et ne pas respirer les vapeurs et brouillards. Assurer une bonne ventilation du poste de travail.
- Mesures d'hygiène : Se laver les mains et toute autre zone exposée avec un savon doux et de l'eau, avant de manger, de boire, de fumer, et avant de quitter le travail. Produit à manipuler en suivant une bonne hygiène industrielle et des procédures de sécurité.

7.2. Conditions d'un stockage sûr, y compris d'éventuelles incompatibilités

- Conditions de stockage : Garder les conteneurs fermés hors de leur utilisation.
- Produits incompatibles : Acides forts. Bases fortes. Oxydants forts.
- Chaleur et sources d'ignition : Tenir à l'écart de la chaleur, des étincelles et des flammes.
- Interdictions de stockage en commun : Matières incompatibles.
- Lieu de stockage : Conserver dans un endroit sec, frais et bien ventilé.

7.3. Utilisation(s) finale(s) particulière(s)

Lubrifiant.

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

8.1. Paramètres de contrôle

8.1.1. Valeurs limites nationales d'exposition professionnelle et biologiques

Distillates (pétroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
IOEL TWA	5 mg/m ³ 8-h (inhalable)

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	White spirit Type 3
IOEL TWA [ppm]	20 ppm
IOELV STEL (mg/m ³)	290 mg/m ³
IOELV STEL (ppm)	50 ppm
Notes	Skin. (Year of adoption 2007)
Référence réglementaire	SCOEL Recommendations
1,2,4-triméthylbenzène (95-63-6)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	1,2,4-Trimethylbenzene
IOEL TWA	100 mg/m ³
IOEL TWA [ppm]	20 ppm
Référence réglementaire	COMMISSION DIRECTIVE 2000/39/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	1,2,4-Triméthylbenzène
VME [mg/m ³]	100 mg/m ³
VME (OEL TWA) [ppm]	20 ppm
VLE [mg/m ³]	250 mg/m ³
VLE [ppm]	50 ppm
Note (FR)	Valeurs réglementaires contraignantes
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Mesitylene (Trimethylbenzenes)
IOEL TWA	100 mg/m ³
IOEL TWA [ppm]	20 ppm
Référence réglementaire	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	1,3,5-Triméthylbenzène (Mésitylène)
VME [mg/m ³]	100 mg/m ³
VME (OEL TWA) [ppm]	20 ppm
VLE [mg/m ³]	250 mg/m ³
VLE [ppm]	50 ppm

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
Note (FR)	Valeurs réglementaires contraignantes
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
1,2,3-Trimethylbenzene (526-73-8)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	1,2,3-Trimethylbenzene
IOEL TWA	100 mg/m ³
IOEL TWA [ppm]	20 ppm
Référence réglementaire	COMMISSION DIRECTIVE 2000/39/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	1,2,3-Triméthylbenzène
VME [mg/m ³]	100 mg/m ³
VME (OEL TWA) [ppm]	20 ppm
VLE [mg/m ³]	250 mg/m ³
VLE [ppm]	50 ppm
Note (FR)	Valeurs réglementaires contraignantes
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Xylenes (1330-20-7)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
IOEL TWA [ppm]	50 ppm
IOELV STEL (mg/m ³)	442 mg/m ³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Référence réglementaire	COMMISSION DIRECTIVE 2000/39/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	Xylène: mélange d'isomères
VME [mg/m ³]	221 mg/m ³
VME (OEL TWA) [ppm]	50 ppm
VLE [mg/m ³]	442 mg/m ³
VLE [ppm]	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

éthylbenzène (100-41-4)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Ethylbenzene
IOEL TWA	442 mg/m ³
IOEL TWA [ppm]	100 ppm
IOELV STEL (mg/m ³)	884 mg/m ³
IOELV STEL (ppm)	200 ppm
Notes	Skin
Référence réglementaire	COMMISSION DIRECTIVE 2000/39/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	Ethylbenzène
VME [mg/m ³]	88,4 mg/m ³
VME (OEL TWA) [ppm]	20 ppm
VLE [mg/m ³]	442 mg/m ³
VLE [ppm]	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Naphthalene (91-20-3)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Naphthalene
IOEL TWA	50 mg/m ³
IOEL TWA [ppm]	10 ppm
Notes	(Year of adoption 2010)
Référence réglementaire	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
France - Valeurs Limites d'exposition professionnelle	
Nom local	Naphtalène
VME [mg/m ³]	50 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
Note (FR)	Valeurs recommandées/admises; substance classée cancérogène de catégorie 2
Référence réglementaire	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Diphenylamine (122-39-4)	
France - Valeurs Limites d'exposition professionnelle	
Nom local	Diphénylamine
VME [mg/m ³]	10 mg/m ³
Note (FR)	Valeurs recommandées/admises

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Diphenylamine (122-39-4)	
Référence réglementaire	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
cumene (98-82-8)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	2-Phenylpropane (Cumene)
IOEL TWA	100 mg/m ³
IOEL TWA [ppm]	10 ppm
IOELV STEL (mg/m ³)	250 mg/m ³
IOELV STEL (ppm)	50 ppm
Notes	Skin. During exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL)
Référence réglementaire	COMMISSION DIRECTIVE (EU) 2019/1831
France - Valeurs Limites d'exposition professionnelle	
Nom local	Cumène (Isopropylbenzène; 2-phénylpropane)
VME [mg/m ³]	50 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE [mg/m ³]	250 mg/m ³
VLE [ppm]	50 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
ethylenediamine (107-15-3)	
France - Valeurs Limites d'exposition professionnelle	
Nom local	1,2-Diaminoéthane (Ethylenediamine)
VME [mg/m ³]	25 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE [mg/m ³]	35 mg/m ³
VLE [ppm]	15 ppm
Note (FR)	Valeurs recommandées/admises
Référence réglementaire	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Benzene (71-43-2)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Benzene
IOEL TWA	3,25 mg/m ³
IOEL TWA [ppm]	1 ppm
Notes	Skin

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Benzene (71-43-2)	
Référence réglementaire	DIRECTIVE (EU) 2019/130 (amending Directive 2004/37/EC)
UE - Limite contraignante d'exposition professionnelle (BOEL)	
Nom local	Benzene
BOEL TWA	3,25 mg/m ³ (Limit value until 5 April 2024) 1,65 mg/m ³ (Limit value from 5 April 2024 until 5 April 2026) 0,66 mg/m ³ (Limit value from 5 April 2026)
BOEL TWA [ppm]	1 ppm (Limit value until 5 April 2024) 0,5 ppm (Limit value from 5 April 2024 until 5 April 2026) 0,2 ppm (Limit value from 5 April 2026)
Notes	Skin (Substantial contribution to the total body burden via dermal exposure possible)
Référence réglementaire	DIRECTIVE (EU) 2022/431 (amending Directive 2004/37/EC)
UE - Biological Limit Value (BLV)	
Nom local	Benzene
BLV	28 µg/l Parameter: benzene - Medium: blood - Sampling time: immediately end of shift 46 µg/g créatinine Parameter: phenylmercapturic - Medium: urine - Sampling time: end of exposure/shift
Référence réglementaire	SCOEL List of recommended health-based BLVs and BGVs
France - Valeurs Limites d'exposition professionnelle	
Nom local	Benzène
VME [mg/m ³]	3,25 mg/m ³
VME (OEL TWA) [ppm]	1 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Toluene (108-88-3)	
UE - Limite indicative d'exposition professionnelle (IOEL)	
Nom local	Toluene
IOEL TWA	192 mg/m ³
IOEL TWA [ppm]	50 ppm
IOELV STEL (mg/m ³)	384 mg/m ³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Référence réglementaire	COMMISSION DIRECTIVE 2006/15/EC
France - Valeurs Limites d'exposition professionnelle	
Nom local	Toluène
VME [mg/m ³]	76,8 mg/m ³
VME (OEL TWA) [ppm]	20 ppm

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Toluene (108-88-3)	
VLE [mg/m ³]	384 mg/m ³
VLE [ppm]	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Référence réglementaire	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
Calcium carbonate (471-34-1)	
France - Valeurs Limites d'exposition professionnelle	
Nom local	Calcium (carbonate de) (Calcite) (Marbre)
VME [mg/m ³]	10 mg/m ³
Note (FR)	Valeurs recommandées/admises
Référence réglementaire	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)

8.1.2. Procédures de suivi recommandées

Pas d'informations complémentaires disponibles

8.1.3. Contaminants atmosphériques formés

Pas d'informations complémentaires disponibles

8.1.4. DNEL et PNEC

Pas d'informations complémentaires disponibles

8.1.5. Bande de contrôle

Pas d'informations complémentaires disponibles

8.2. Contrôles de l'exposition

8.2.1. Contrôles techniques appropriés

Contrôles techniques appropriés:

Éviter les éclaboussures. Assurer une bonne ventilation du poste de travail.

8.2.2. Équipements de protection individuelle

Équipement de protection individuelle:

Éviter toute exposition inutile.

8.2.2.1. Protection des yeux et du visage

Protection oculaire:

En cas d'éclaboussures ou des aérosols: des lunettes de protection. EN166

8.2.2.2. Protection de la peau

Protection des mains:

Porter des gants appropriés. gants en caoutchouc nitrile. EN374

8.2.2.3. Protection des voies respiratoires

Protection des voies respiratoires:

En cas de ventilation insuffisante, porter un appareil respiratoire approprié. Respirateur agréé. EN 136. EN 143

8.2.2.4. Protection contre les risques thermiques

Pas d'informations complémentaires disponibles

8.2.3. Contrôle de l'exposition de l'environnement

Contrôle de l'exposition de l'environnement:

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Empêcher toute fuite ou déversement. Empêcher tout ruissellement d'eau contaminée.

Autres informations:

Ne pas manger, boire ou fumer en manipulant ce produit.

RUBRIQUE 9: Propriétés physiques et chimiques

9.1. Informations sur les propriétés physiques et chimiques essentielles

État physique	: Liquide
Couleur	: ambré.
Odeur	: pétrole.
Seuil olfactif	: Pas disponible
Point de fusion	: Pas disponible
Point de congélation	: Pas disponible
Point d'ébullition	: Pas disponible
Inflammabilité	: Pas disponible
Limites d'explosivité	: Pas disponible
Limite inférieure d'explosion	: Pas disponible
Limite supérieure d'explosivité (LSE)	: Pas disponible
Point d'éclair	: > 100 °C
Température d'auto-inflammation	: Pas disponible
Température de décomposition	: Pas disponible
pH	: Pas disponible
Viscosité, cinématique	: > 20 mm ² /s @ 40 °C
Solubilité	: Pas disponible
Log Kow	: Pas disponible
Pression de vapeur	: Pas disponible
Pression de vapeur à 50 °C	: Pas disponible
Masse volumique	: ≈ 7,25 lb/gal
Densité relative	: ≈ 0,9
Densité relative de vapeur à 20 °C	: Pas disponible
La taille des particules	: Non applicable
Distribution granulométrique	: Non applicable
Forme des particules	: Non applicable
Rapport hauteur / largeur des particules	: Non applicable
État d'agrégation des particules	: Non applicable
État d'agglomération des particules	: Non applicable
Surface spécifique des particules	: Non applicable
Poussière de particules	: Non applicable

9.2. Autres informations

9.2.1. Informations concernant les classes de danger physique

Pas d'informations complémentaires disponibles

9.2.2. Autres caractéristiques de sécurité

Pas d'informations complémentaires disponibles

RUBRIQUE 10: Stabilité et réactivité

10.1. Réactivité

Aucune réaction dangereuse connue.

10.2. Stabilité chimique

Stable dans les conditions d'utilisation et de stockage recommandées (voir section 7).

10.3. Possibilité de réactions dangereuses

Polymérisation dangereuse ne se produira pas.

10.4. Conditions à éviter

Chaleur.

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

10.5. Matières incompatibles

Acides forts. Bases fortes. Oxydants forts.

10.6. Produits de décomposition dangereux

Hydrocarbure. Oxydes de carbone (CO, CO₂).

RUBRIQUE 11: Informations toxicologiques

11.1. Informations sur les classes de danger telles que définies dans le règlement (CE) n° 1272/2008

Toxicité aiguë (orale) : Non classé
 Toxicité aiguë (cutanée) : Non classé
 Toxicité aiguë (Inhalation) : Non classé

Distillates (pétroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)

DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
CL50 Inhalation rat	> 5,53 mg/l/4h

Distillates (pétroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

DL50 Orale rat	> 5000 mg/kg de poids corporel
DL50 Cutanée lapin	> 2000 mg/kg de poids corporel
CL50 Inhalation rat	> 10,5 mg/l/4h

Antimony, tris(dipentylcarbamodithioato-S,S')- (15890-25-2)

DL50 Orale rat	1640 mg/kg
DL50 Cutanée lapin	1600 mg/kg

1-Decene, homopolymer, hydrogenated (68037-01-4)

DL50 Orale rat	> 5000 mg/kg de poids corporel
DL50 Cutanée rat	> 2000 mg/kg
CL50 Inhalation rat (poussière / brouillard)	> 5,2 mg/l/4h

sulfurized isobutylene (68511-50-2)

DL50 Orale rat	8600 mg/kg
----------------	------------

Oleylamine (112-90-3)

DL50 Orale rat	1689 mg/kg
----------------	------------

Naphtha (pétroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)

DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
CL50 Inhalation rat	> 5610 mg/m ³

1,2,4-triméthylbenzène (95-63-6)

DL50 Orale rat	3415 mg/kg
DL50 Cutanée rat	3440 mg/kg
DL50 Cutanée lapin	> 3160 mg/kg Source: International Uniform Chemical Information Database
CL50 Inhalation rat	10,2 mg/l air Animal: rat, Remarks on results: other:

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

1,2,4-triméthylbenzène (95-63-6)	
CL50 Inhalation rat [ppm]	954 ppm
CL50 Inhalation rat (vapeurs)	18 mg/l Source: Corporate Solution From Thomson Micromedex
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
DL50 Orale rat	5000 mg/kg
DL50 Cutanée rat	> 4 ml/kg
CL50 Inhalation rat	24000 mg/m ³
Xylenes (1330-20-7)	
DL50 Orale rat	> 3500 mg/kg
DL50 Cutanée lapin	12126 mg/kg de poids corporel Animal: rabbit, Animal sex: male, Remarks on results: other:
CL50 Inhalation rat [ppm]	5922 ppm
éthylbenzène (100-41-4)	
DL50 Orale rat	3500 mg/kg
DL50 Cutanée lapin	17,8 ml/kg
CL50 Inhalation rat [ppm]	< 1500 ppm
Naphthalene (91-20-3)	
DL50 Orale rat	> 2000 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
DL50 Cutanée lapin	2500 mg/kg Source: ChemIDplus
CL50 Inhalation rat	> 0,4 mg/l air Animal: rat, Guideline: other:, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity), Remarks on results: other:
CL50 Inhalation rat (vapeurs)	> 0,4 mg/l Source: ECHA
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO <3%) (64742-65-0)	
DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
CL50 Inhalation rat	2,18 mg/l
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
DL50 Orale rat	2000 – 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
DL50 Orale rat	3100 mg/kg
DL50 Cutanée rat	> 2002 mg/kg
CL50 Inhalation rat	> 2,3 mg/l/4h
Polybutene (9003-29-6)	
DL50 Orale rat	> 34600 mg/kg

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Polybutene (9003-29-6)	
DL50 Cutanée lapin	> 10250 mg/kg
CL50 Inhalation rat	> 17,3 mg/l/4h
Amines, C12-14-alkyl, C6-10-alkyl phosphates (68603-55-4)	
DL50 Orale rat	500 (500 – 1000) mg/kg
cumene (98-82-8)	
DL50 Orale rat	4000 mg/kg
DL50 Cutanée lapin	10600 mg/kg
CL50 Inhalation rat	22,1 mg/l
CL50 Inhalation rat [ppm]	4510 ppm/4h
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
Zinc alkyl dithiophosphate (113706-15-3)	
DL50 Orale rat	2600 mg/kg
DL50 Cutanée lapin	> 3160 mg/kg
Benzene (71-43-2)	
DL50 Orale rat	5970 mg/kg OECD Guideline 401 (Acute Oral Toxicity)
DL50 Cutanée lapin	> 9,4 mg/kg OECD Guideline 402 (Acute Dermal Toxicity)
CL50 Inhalation rat	43,7 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)
Toluene (108-88-3)	
DL50 Orale rat	5580 mg/kg EU Method B.
DL50 Cutanée lapin	> 5000 mg/kg Source: ECHA
CL50 Inhalation rat	> 20 mg/l/4h OECD Guideline 403
CL50 Inhalation rat (vapeurs)	> 20 mg/l Source: ECHA
Isobutene-butene polymer (9003-29-6)	
DL50 Orale rat	> 34600 mg/kg
DL50 Cutanée lapin	> 10250 mg/kg
CL50 Inhalation rat	> 17300 mg/m ³
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	
DL50 Orale rat	3600 mg/kg
DL50 Cutanée lapin	> 20000 mg/kg
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
DL50 Orale rat	26100 mg/kg

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Calcium carbonate (471-34-1)	
DL50 Orale rat	> 2000 mg/kg de poids corporel Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
DL50 Cutanée rat	> 2000 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
CL50 Inhalation rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
CL50 Inhalation rat (poussière / brouillard)	> 3 mg/l Source: ECHA
Distillates (petroleum), hydrotreated light naphthenic (DMSO <3%) (64742-53-6)	
DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée lapin	> 2000 mg/kg
CL50 Inhalation rat	> 5,53 mg/l/4h
Tricresylphosphate (1330-78-5)	
DL50 Orale rat	> 20000 mg/kg
CL50 Inhalation rat	> 11,1 mg/l 1 h
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%) (72623-86-0)	
DL50 Orale rat	> 5000 mg/kg de poids corporel
DL50 Cutanée lapin	> 2000 mg/kg de poids corporel/jour
Phenol, dodecyl-, branched (121158-58-5)	
DL50 Orale rat	> 2000 mg/kg de poids corporel
DL50 Cutanée lapin	> 2000 mg/kg de poids corporel
bis(nonylphenyl)amine (36878-20-3)	
DL50 Orale rat	> 5000 mg/kg
DL50 Cutanée rat	> 2000 mg/kg
Toxicité aiguë inconnue (CLP: Classification, étiquetage, emballage.) - FDS	: le mélange contient 8,1% de composants dont la toxicité aiguë est inconnue (Oral) le mélange contient 8,6% de composants dont la toxicité aiguë est inconnue (Cutané) le mélange contient 8,6% de composants dont la toxicité aiguë est inconnue (Inhalation (Poussières/brouillards))
Corrosion cutanée/irritation cutanée	: Non classé. (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Lésions oculaires graves/irritation oculaire	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Sensibilisation respiratoire ou cutanée	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Mutagénicité sur les cellules germinales	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Cancérogénicité	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Xylenes (1330-20-7)	
Groupe IARC	3 - Not classifiable

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

éthylbenzène (100-41-4)	
Groupe IARC	2B - Cancérogène possible pour l'humain
Naphthalene (91-20-3)	
Groupe IARC	2B - Cancérogène possible pour l'humain
Diphenylamine (122-39-4)	
Groupe IARC	2B - Cancérogène possible pour l'humain
cumene (98-82-8)	
Groupe IARC	2B - Cancérogène possible pour l'humain
Benzene (71-43-2)	
Groupe IARC	1 - Cancérogène pour l'homme
Toluene (108-88-3)	
Groupe IARC	3 - Not classifiable
Toxicité pour la reproduction	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Naphthalene (91-20-3)	
LOAEL (animal/femelle, F1)	450 mg/kg de poids corporel Animal: rat, Animal sex: female, Guideline: other:
Toxicité spécifique pour certains organes cibles (exposition unique)	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
Oleylamine (112-90-3)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut irriter les voies respiratoires.
1,2,4-triméthylbenzène (95-63-6)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut irriter les voies respiratoires.
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut irriter les voies respiratoires.
1,2,3-Trimethylbenzene (526-73-8)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut irriter les voies respiratoires.
cumene (98-82-8)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut irriter les voies respiratoires.
Toluene (108-88-3)	
Toxicité spécifique pour certains organes cibles (exposition unique)	Peut provoquer somnolence ou vertiges.
Toxicité spécifique pour certains organes cibles (exposition répétée)	: Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Oleylamine (112-90-3)	
Toxicité spécifique pour certains organes cibles (exposition répétée)	Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
1,2,4-triméthylbenzène (95-63-6)	
NOAEL (oral, rat, 90 jours)	600 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapeur, 90 jours)	1,8 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Xylenes (1330-20-7)	
LOAEL (oral, rat, 90 jours)	150 mg/kg de poids corporel Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
éthylbenzène (100-41-4)	
NOAEL (oral, rat, 90 jours)	75 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Toxicité spécifique pour certains organes cibles (exposition répétée)	Risque présumé d'effets graves pour les organes (organes de l'ouïe) à la suite d'expositions répétées ou d'une exposition prolongée.
Naphthalene (91-20-3)	
LOAEL (oral, rat, 90 jours)	400 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation, rat, vapeur, 90 jours)	0,011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 jours)	200 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (cutané, rat/lapin, 90 jours)	1000 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Diphenylamine (122-39-4)	
Toxicité spécifique pour certains organes cibles (exposition répétée)	Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
Benzene (71-43-2)	
LOAEL (oral, rat, 90 jours)	25 mg/kg de poids corporel/jour OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 jours)	100 mg/kg de poids corporel/jour OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, gaz, 90 jours)	30 ppmv/6h/jour OECD Guideline 412 / 413
Toxicité spécifique pour certains organes cibles (exposition répétée)	Risque avéré d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
Toluene (108-88-3)	
LOAEC (inhalation, rat, gaz, 90 jours)	1250 ppmv/6h/jour
NOAEL (oral, rat, 90 jours)	625 mg/kg de poids corporel/jour EU Method B.26.
NOAEC (inhalation, rat, gaz, 90 jours)	300 ppmv/6h/jour OECD Guideline 453

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Toluene (108-88-3)	
Toxicité spécifique pour certains organes cibles (exposition répétée)	Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 jours)	1000 mg/kg de poids corporel Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, poussière/brouillard/fumée, 90 jours)	≥ 0,212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Distillates (petroleum), hydrotreated light naphthenic (DMSO <3%) (64742-53-6)	
LOAEL (oral, rat, 90 jours)	125 mg/kg de poids corporel/jour
NOAEL (subchronique, oral, animal/mâle, 90 jours)	< 125 mg/kg de poids corporel NOAEL for heavy paraffinic distillate aromatic extract could not be identified and is less than 125 mg/kg/day when administered orally.

Danger par aspiration : Non classé. (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Viscosité, cinématique > 20 mm²/s @ 40 °C

11.2. Informations sur les autres dangers

11.2.1. Propriétés perturbant le système endocrinien

Composant	
tetrapropenylphenol(74499-35-7)	La substance est identifiée pour avoir des propriétés de perturbation endocrinienne mais il n'y a pas de données supplémentaires disponibles
Phenol, dodecyl-, branched(121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission
Phenol, dodecyl-, branched (121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission

11.2.2. Autres informations

RUBRIQUE 12: Informations écologiques

12.1. Toxicité

Ecologie - eau : Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.
Dangers pour l'environnement aquatique inconnus (CLP) : Contient 9,23 % de composants dont la toxicité pour le milieu aquatique est inconnue

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Dangers pour le milieu aquatique, à court terme (aiguë) : Non classé (Compte tenu des données disponibles, les critères de classification ne sont pas remplis)
 Dangers pour le milieu aquatique, à long terme (chronique) : Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)	
EC50 crustacea	> 10000 mg/l
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
CL50 poisson 1	> 100 mg/l
1-Decene, homopolymer, hydrogenated (68037-01-4)	
CL50 poisson 1	> 750 mg/l
EC50 crustacea	190 mg/l
NOEC (aigu)	1000 mg/l
sulfurized isobutylene (68511-50-2)	
CL50 poisson 1	< 1000 mg/l
EC50 crustacea	1000 mg/l
CE50 autres organismes aquatiques 1	29 (29 – 39) mg/l
CEr50 algues	> 100 mg/l
NOEC (aigu)	< 1000 mg/l
NOEC chronique crustacé	1000 mg/l
NOEC chronique algues	10 mg/l
Oleylamine (112-90-3)	
CL50 poisson 1	0,11 mg/l
EC50 crustacea	0,011 mg/l
NOEC chronique algues	≤ 0,01 mg/l
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)	
CL50 poisson 1	8,2 mg/l
CL50 autres organismes aquatiques 1	2,6 mg/l Source: IUCLID
1,2,4-triméthylbenzène (95-63-6)	
CL50 poisson 1	7,72 mg/l
CL50 autres organismes aquatiques 1	3,6 mg/l
EC50 crustacea	6,14 mg/l Source: International Uniform Chemical Information Database
CE50 autres organismes aquatiques 1	2,356 mg/l
CE50 96h - Algues [1]	2356 mg/l Test organisms (species): other:
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
CL50 poisson 1	12,52 mg/l
CL50 autres organismes aquatiques 1	6 mg/l
CE50 autres organismes aquatiques 1	25 mg/l

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

1,2,3-Trimethylbenzene (526-73-8)	
CL50 poisson 1	2,792 mg/l Source: Ecological Structure Activity Relationships
CE50 96h - Algues [1]	2,29 mg/l Source: Ecological Structure Activity Relationships
Xylenes (1330-20-7)	
CL50 poisson 1	2,6 mg/l Source: ECHA
EC50 crustacea	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronique)	3,16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronique poisson	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
éthylbenzène (100-41-4)	
CL50 poisson 1	5,1 mg/l
CE50 autres organismes aquatiques 1	7,7 mg/l
CE50 72h - Algues [1]	5,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
CE50 72h - Algues [2]	4,9 mg/l Test organisms (species): Skeletonema costatum
CE50 96h - Algues [1]	3,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
CE50 96h - Algues [2]	7,7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronique)	1,7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (aigu)	3,3 mg/l
NOEC (chronique)	0,96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
Naphthalene (91-20-3)	
CL50 poisson 1	1,6 mg/l
CL50 - Poisson [2]	1 (1 – 6,5) mg/l Pimpephales promelas
EC50 crustacea	2,16 mg/l
CE50 autres organismes aquatiques 1	33 mg/l
LOEC (aigu)	3,2 mg/l
NOEC (aigu)	1,8 mg/l
NOEC (chronique)	0,59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
Diphenylamine (122-39-4)	
CL50 poisson 1	4,14 ppm
EC50 crustacea	2,46 mg/l
CE50 autres organismes aquatiques 1	0,36 mg/l
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
CL50 poisson 1	4,5 mg/l
EC50 crustacea	23 mg/l
CEr50 algues	21 mg/l

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
NOEC (aigu)	1,8 mg/l
NOEC chronique crustacé	0,8 mg/l
Polybutene (9003-29-6)	
CL50 poisson 1	> 1000 mg/l
EC50 crustacea	> 1000 mg/l
Amines, C12-14-alkyl, C6-10-alkyl phosphates (68603-55-4)	
CL50 poisson 1	1 (1 – 10) mg/l
cumene (98-82-8)	
CL50 poisson 1	4,8 mg/l
CL50 - Poisson [2]	4,8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 crustacea	2,14 mg/l Test organisms (species): Daphnia magna
CE50 autres organismes aquatiques 1	2,14 mg/l
CE50 72h - Algues [1]	2,01 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
CE50 72h - Algues [2]	1,29 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
CEr50 algues	2,01 mg/l Source: ECHA
NOEC (aigu)	1,9 mg/l
NOEC (chronique)	0,35 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronique poisson	0,38 mg/l Test organisms (species): other: Duration: '28 d'
Zinc alkyl dithiophosphate (113706-15-3)	
CL50 poisson 1	4,5 mg/l 96 h Rainbow trout
tetrapropenylphenol (74499-35-7)	
NOEC (chronique)	0,002 mg/l
Benzene (71-43-2)	
CL50 poisson 1	5,3 mg/l OECD Guideline 203 (Fish, Acute Toxicity Test)
EC50 crustacea	10 mg/l OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
CE50 72h - Algues [1]	29 mg/l Source: NITE
CEr50 algues	100 mg/l OECD Guideline 201 (Alga, Growth Inhibition Test)
LOEC (chronique)	1,6 mg/l 32 d
NOEC chronique crustacé	3 mg/l
Toluene (108-88-3)	
CL50 poisson 1	5,5 mg/l
EC50 crustacea	3,78 mg/l Source: ECHA

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Toluene (108-88-3)	
CE50 - Crustacés [2]	3,78 mg/l
CEr50 algues	134 mg/l
LOEC (chronique)	2,77 mg/l
NOEC chronique poisson	1,39 mg/l
NOEC chronique crustacé	0,74 mg/l
Isobutene-butene polymer (9003-29-6)	
CL50 poisson 1	> 1000 mg/l
EC50 crustacea	> 1000 mg/l
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
CL50 poisson 1	10 (10 – 35) mg/l Pimephales promelas OECD GDL 203 (water accomodated fraction)
EC50 crustacea	1 (1 – 1,5) mg/l OECD GDL 202 (water accomodated fraction)
NOEC (aigu)	10 mg/l Pimephales promelas OECD GDL 203 (water accomodated fraction)
NOEC chronique crustacé	< 1 mg/l
Calcium carbonate (471-34-1)	
CL50 poisson 1	> 100 % v/v, 96 h
EC50 crustacea	> 100 % v/v, 48 h
CE50 72h - Algues [1]	> 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
CE50 96h - Algues [1]	22000 mg/l Source: Ecological Structure Activity Relationships
Tricresylphosphate (1330-78-5)	
CL50 poisson 1	0,6 mg/l 4 d
EC50 crustacea	0,146 mg/l 2 d
CE50 72h - Algues [1]	0,4042 mg/l 3 d
NOEC (aigu)	0,56 mg/l 4 d
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%) (72623-86-0)	
CL50 poisson 1	> 100 mg/l
EC50 crustacea	> 10000 mg/l
NOEC (aigu)	> 1000 mg/l
bis(nonylphenyl)amine (36878-20-3)	
CL50 poisson 1	> 100 mg/l

12.2. Persistance et dégradabilité

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil	
Persistance et dégradabilité	Peut entraîner des effets néfastes à long terme pour l'environnement.
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
Persistance et dégradabilité	Difficilement biodégradable.
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Persistance et dégradabilité	Facilement biodégradable.
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
Persistance et dégradabilité	Difficilement biodégradable.
Biodégradation	0 % O2 consumption, 192h
éthylbenzène (100-41-4)	
Persistance et dégradabilité	Non établi.
Distillates (petroleum), solvant-dewaxed heavy paraffinic (DMSO <3%) (64742-65-0)	
Persistance et dégradabilité	Non établi.
Diphenylamine (122-39-4)	
Persistance et dégradabilité	Non établi.
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
Biodégradation	1,5 % 28 days
Polybutene (9003-29-6)	
Persistance et dégradabilité	Ce produit n'est pas présumé biodégradable.
Amines, C12-14-alkyl, C6-10-alkyl phosphates (68603-55-4)	
Biodégradation	62 %
cumene (98-82-8)	
Persistance et dégradabilité	Peut entraîner des effets néfastes à long terme pour l'environnement.
Distillates (petroleum), solvant-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
Persistance et dégradabilité	Non établi.
Zinc alkyl dithiophosphate (113706-15-3)	
Persistance et dégradabilité	Difficilement biodégradable.
tetrapropenylphenol (74499-35-7)	
Persistance et dégradabilité	Produit persistant.

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Benzene (71-43-2)	
Persistance et dégradabilité	Facilement biodégradable.
Toluene (108-88-3)	
Persistance et dégradabilité	Facilement biodégradable.
Isobutene-butene polymer (9003-29-6)	
Persistance et dégradabilité	Ce produit n'est pas présumé biodégradable.

12.3. Potentiel de bioaccumulation

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil	
Potentiel de bioaccumulation	Non établi.
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Potentiel de bioaccumulation	Ne devrait pas y avoir de bioaccumulation.
sulfurized isobutylene (68511-50-2)	
Log Pow	> 3
Oleylamine (112-90-3)	
Log Pow	7,5
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)	
Log Pow	2,1 – 6 Source: IUCLID
1,2,4-triméthylbenzène (95-63-6)	
Log Pow	3,78 Source: National Library of Medicine/Hazardous Substances Data Bank
mésitylène; 1,3,5-triméthylbenzène (108-67-8)	
FBC poissons 1	23 – 382 concentration 150ppb
FBC poisson 2	42 – 328 concentration 15ppb
Log Pow	3,42
1,2,3-Trimethylbenzene (526-73-8)	
Log Pow	3,7 Source: International Chemical Safety Cards
Xylenes (1330-20-7)	
FBC poissons 1	1,3 mg/l
Log Pow	3,15 Source: HSDB
Potentiel de bioaccumulation	Ne devrait pas y avoir de bioaccumulation.

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

éthylbenzène (100-41-4)	
Log Pow	3,15 Source: HSDB
Potentiel de bioaccumulation	Non établi.
Naphthalene (91-20-3)	
FBC poissons 1	≥ 427 (427 – 1158)
Log Pow	3,3 Source: hsbdb
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO <3%) (64742-65-0)	
Potentiel de bioaccumulation	Non établi.
Diphenylamine (122-39-4)	
Potentiel de bioaccumulation	Non établi.
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
Log Kow	0,56
Polybutene (9003-29-6)	
Potentiel de bioaccumulation	Ce produit ne est pas bio-accumulation.
cumene (98-82-8)	
Log Pow	3,66 Source: HSDB
Potentiel de bioaccumulation	Non établi.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
Potentiel de bioaccumulation	Non établi.
Zinc alkyl dithiophosphate (113706-15-3)	
Log Pow	0,9
tetrapropenylphenol (74499-35-7)	
Log Pow	7,17
Benzene (71-43-2)	
FBC poissons 1	3,5 – 4,4
Facteur de bioconcentration (BCF REACH)	0
Log Pow	1,83
Toluene (108-88-3)	
Facteur de bioconcentration (BCF REACH)	90
Log Pow	2,73 Source: HSDB
Log Kow	2,73
Isobutene-butene polymer (9003-29-6)	
Potentiel de bioaccumulation	Ce produit ne est pas bio-accumulation.
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	
Log Pow	1,67

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Tricresylphosphate (1330-78-5)	
Log Kow	5,93

12.4. Mobilité dans le sol

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil	
Ecologie - sol	Pas d'informations complémentaires disponibles.

1,2,3-Trimethylbenzene (526-73-8)	
Mobilité dans le sol	630 Source: National Library of Medicine/Hazardous Substances Data Bank

Polybutene (9003-29-6)	
Ecologie - sol	Cette substance, qui est peu soluble et flotte à la surface, n'est pas présumée se fractionner dans l'eau.

Zinc alkyl dithiophosphate (113706-15-3)	
Ecologie - sol	Absorbe les particules du sol et ne sera pas mobile.

Isobutene-butene polymer (9003-29-6)	
Ecologie - sol	Cette substance, qui est peu soluble et flotte à la surface, n'est pas présumée se fractionner dans l'eau.

Calcium carbonate (471-34-1)	
Mobilité dans le sol	4,971 Source: Quantitative Structure Activity Relation

12.5. Résultats des évaluations PBT et vPvB

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil. Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil	
vPvB: pas encore évalué	

Composant	
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
tetrapropenylphenol (74499-35-7)	PBT: non pertinent – pas d'enregistrement requis vPvB: non pertinent – pas d'enregistrement requis

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Composant	
	Summary: tetrapropenylphenol is considered to clearly meet the T criterion, and is likely to meet the P and vP criteria with a reasonable degree of confidence. It does not meet the TGD B or vB criteria, and so is not considered a PBT substance according to the EU criteria.
Phenol, dodecyl-, branched (121158-58-5)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Phenol, dodecyl-, branched (121158-58-5)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Toluene (108-88-3)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
Benzene (71-43-2)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII
ethylenediamine (107-15-3)	Cette substance/mélange ne remplit pas les critères PBT du règlement REACH annexe XIII Cette substance/mélange ne remplit pas les critères vPvB du règlement REACH annexe XIII

12.6. Propriétés perturbant le système endocrinien

Composant	
tetrapropenylphenol(74499-35-7)	La substance est identifiée pour avoir des propriétés de perturbation endocrinienne mais il n'y a pas de données supplémentaires disponibles
Phenol, dodecyl-, branched(121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission
Phenol, dodecyl-, branched (121158-58-5)	La substance est incluse dans la liste établie conformément à l'article 59, paragraphe 1, de REACH comme ayant des propriétés perturbant le système endocrinien, ou est reconnue comme ayant des propriétés perturbant le système endocrinien conformément aux critères définis dans le Règlement délégué (UE) 2017/2100 de la Commission ou le Règlement (UE) 2018/605 de la Commission

12.7. Autres effets néfastes

Informations Complémentaires : Pas d'informations complémentaires disponibles

RUBRIQUE 13: Considérations relatives à l'élimination

13.1. Méthodes de traitement des déchets

Recommandations pour l'élimination des déchets : Détruire conformément aux règlements de sécurité locaux/nationaux en vigueur.
Code catalogue européen des déchets (CED) : Pour l'élimination au sein de la CE, le code approprié selon le catalogue européen des déchets (EWC) devrait être utilisé.

RUBRIQUE 14: Informations relatives au transport

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

En conformité avec: ADR / IMDG / IATA / ADN / RID

14.1. Numéro ONU ou numéro d'identification

N° ONU (ADR) : Non applicable
N° ONU (IMDG) : Non applicable
N° ONU (IATA) : Non applicable
N° ONU (ADN) : Non applicable
N° ONU (RID) : Non applicable

14.2. Désignation officielle de transport de l'ONU

Désignation officielle de transport (ADR) : Non applicable
Nom d'expédition (IMDG) : Non applicable
Désignation officielle de transport (IATA) : Non applicable
Désignation officielle de transport (ADN) : Non applicable
Désignation officielle de transport (RID) : Non applicable

14.3. Classe(s) de danger pour le transport

ADR

Classe(s) de danger pour le transport (ADR) : Non applicable

IMDG

Classe(s) de danger pour le transport (IMDG) : Non applicable

IATA

Classe(s) de danger pour le transport (IATA) : Non applicable

ADN

Classe(s) de danger pour le transport (ADN) : Non applicable

RID

Classe(s) de danger pour le transport (RID) : Non applicable

14.4. Groupe d'emballage

Groupe d'emballage (ADR) : Non applicable
Groupe d'emballage (IMDG) : Non applicable
Groupe d'emballage (IATA) : Non applicable
Groupe d'emballage (ADN) : Non applicable
Groupe d'emballage (RID) : Non applicable

14.5. Dangers pour l'environnement

Dangereux pour l'environnement : Non
Polluant marin : Non
Autres informations : Pas d'informations supplémentaires disponibles

14.6. Précautions particulières à prendre par l'utilisateur

Transport par voie terrestre

Non applicable

Transport maritime

Non applicable

Transport aérien

Non applicable

Transport par voie fluviale

Non applicable

Transport ferroviaire

Non applicable

14.7. Transport maritime en vrac conformément aux instruments de l'OMI

Non applicable

RUBRIQUE 15: Informations relatives à la réglementation

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

15.1. Réglementations/législation particulières à la substance ou au mélange en matière de sécurité, de santé et d'environnement

15.1.1. Réglementations UE

Liste de restriction de l'Union européenne (annexe XVII de REACH)		
Code de référence	Applicable sur	Titre de l'entrée ou description
5.	Benzene	Benzène
28.	Benzene	Substances figurant à l'annexe VI, partie 3, du règlement (CE) n° 1272/2008 classées "cancérogène catégorie 1A ou 1B" et énumérées à l'appendice 1 ou à l'appendice 2, respectivement.
29.	Benzene	Substances figurant à l'annexe VI, partie 3, du règlement (CE) n° 1272/2008 classées "mutagènes catégorie 1A ou 1B" et énumérées à l'appendice 3 ou à l'appendice 4, respectivement.
3(a)	Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) ; 1,2,4-triméthylbenzène ; mésitylène ; 1,3,5-triméthylbenzène ; 1,2,3-Triméthylbenzène ; Xylenes ; éthylbenzène ; cumène ; ethylenediamine ; Benzene ; Toluene	Substances ou mélanges qui répondent aux critères pour une des classes ou catégories de danger ci-après, visées à l'annexe I du règlement (CE) n° 1272/2008: Classes de danger 2.1 à 2.4, 2.6 et 2.7, 2.8 types A et B, 2.9, 2.10, 2.12, 2.13 catégories 1 et 2, 2.14 catégories 1 et 2, 2.15 types A à F
3(b)	Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) ; Antimony, tris(dipentylcarbamodithioato-S,S')- ; 1-Decène, homopolymère, hydrogéné ; Amines, polyéthylène poly-, réaction produits avec succinique anhydride polyisobutényl dérivés., borated ; réaction produit de l'acide phosphorique mono- ou di-(C6-C10) alkylester avec alkylamine ; C8-C10 Phosphate ; Oleylamine ; Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) ; Solvant naphtha aromatique léger (pétrole), naphtha à point d'ébullition bas - non spécifié, (benzene <0.1%) ; 1,2,4-triméthylbenzène ; mésitylène ; 1,3,5-triméthylbenzène ; 1,2,3-Triméthylbenzène ; Xylenes ; éthylbenzène ; Distillates (petroleum), solvant-dewaxed heavy paraffinic (DMSO <3%) ; zinc O,O,O',O'-tétrakis(1,3-diméthylbutyl) bis(phosphorodithioate) ; Phenol, dodecyl-, branched ; Phosphorodithioic acid, mixed O,O-bis(1,3-diméthylbutyl and iso-Pr) esters, zinc salts ; Polybutène ; Amines, C12-14-alkyl, C6-10-alkyl phosphates ; 1,3,4-Thiadiazole-2(3O)-thione, 5-(**e**r**t**-dodecylidithio)- ; Phosphoric acid, mono- and di-C6-10-alkyl esters ; cumène ; Distillates (petroleum), solvant-dewaxed heavy paraffinic (DMSO < 3%) ; Zinc alkyl dithiophosphate ; tetrapropénylphénol ; Distillates (petroleum), solvant-affiné léger paraffinic (DMSO < 3%) ; ethylenediamine ; Benzène ; Toluène ; Isobutène-butène polymère ; Phosphorodithioic acid, mixed O,O-bis(2-éthylhexyl and iso-Bu) esters, zinc salts ; Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts ; Distillates (petroleum), solvant-affiné heavy paraffinic (DMSO <3%) ; Benzenesulfonic acid, C10-16-alkyl dérivés., calcium salts ; Sulfonic acids, calcium salts ; Distillates (petroleum), hydrotreated léger naphthénique (DMSO <3%) ; Tricresylphosphate ; Dibutyl phosphite ; Lubrifiants (petroleum), C15-30, hydrotreated neutre à base d'huile (DMSO <3%) ; Zinc bis[O(6-méthylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)- ; Phenol, dodecyl-, branched ; Mineral oil (DMSO <3%)	Substances ou mélanges qui répondent aux critères pour une des classes ou catégories de danger ci-après, visées à l'annexe I du règlement (CE) n° 1272/2008: Classes de danger 3.1 à 3.6, 3.7 effets néfastes sur la fonction sexuelle et la fertilité ou sur le développement, 3.8 effets autres que les effets narcotiques, 3.9 et 3.10

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Liste de restriction de l'Union européenne (annexe XVII de REACH)		
Code de référence	Applicable sur	Titre de l'entrée ou description
3(c)	Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30 Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil; Antimony, tris(dipentylcarbamodithioato-S,S')-; sulfurized isobutylene; Oleylamine; 1,2,4-triméthylbenzène; mésitylène; 1,3,5-triméthylbenzène; zinc O,O,O',O'-tetrakis(1,3-diméthylbutyl) bis(phosphorodithioate); Phenol, dodecyl-, branched; Phosphorodithioic acid, mixed O,O-bis(1,3-diméthylbutyl and iso-Pr) esters, zinc salts; Reaction products of Benzeneamine, N-phenyl- with nonene (branched); Amines, C12-14-alkyl, C6-10-alkyl phosphates; cumene; Zinc alkyl dithiophosphate; tetrapropenylphenol; Toluene; Phosphorodithioic acid, mixed O,O-bis(2-éthylhexyl and iso-Bu) esters, zinc salts; Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts; Tricresylphosphate; Benzenamine, N-phenyl-, styrenated; Zinc bis[O(6-méthylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)-; Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased; Phenol, dodecyl-, branched; bis(nonylphenyl)amine	Substances ou mélanges qui répondent aux critères pour une des classes ou catégories de danger ci-après, visées à l'annexe I du règlement (CE) n° 1272/2008: Classe de danger 4.1
30.	Phenol, dodecyl-, branched; tetrapropenylphenol; Phenol, dodecyl-, branched	Substances figurant à l'annexe VI, partie 3, du règlement (CE) n° 1272/2008 classées "toxiques pour la reproduction catégorie 1A ou 1B" et énumérées à l'appendice 5 ou à l'appendice 6, respectivement.
40.	Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%); 1,2,4-triméthylbenzène; mésitylène; 1,3,5-triméthylbenzène; 1,2,3-Triméthylbenzène; Xylenes; éthylbenzène; cumene; ethylenediamine; Benzene; Toluene	Substances classées comme gaz inflammables, catégorie 1 ou 2, liquides inflammables, catégorie 1, 2 ou 3, matières solides inflammables, catégorie 1 ou 2, substances et mélanges qui, au contact de l'eau, dégagent des gaz inflammables, catégorie 1, 2 ou 3, liquides pyrophoriques, catégorie 1, ou matières solides pyrophoriques, catégorie 1, qu'elles figurent ou non à l'annexe VI, partie 3, du règlement (CE) n° 1272/2008.
48.	Toluene	Toluène
72.	Benzene	Les substances énumérées dans la colonne 1 du tableau figurant dans l'appendice 12

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Contient une substance de la liste candidate REACH: Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP) (EC 310-154-3, CAS 121158-58-5), Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP) (EC 310-154-3, CAS 74499-35-7), Ethylènediamine (EC 203-468-6, CAS 107-15-3), Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP) (EC 310-154-3, CAS 121158-58-5)

Ne contient aucune substance listée à l'Annexe XIV de REACH

Substances soumises au règlement (UE) no 649/2012 du Parlement européen et du Conseil du 4 juillet 2012 concernant l'exportation et l'importation de produits chimiques dangereux: Diphénylamine (122-39-4), Benzène (71-43-2)

Substance (s) non soumise au règlement (CE) n ° No 2019/1021 du Parlement européen et du Conseil du 20 juin 2019 concernant les polluants organiques persistants.

15.1.2. Directives nationales

France	
Maladies professionnelles	
Code	Description
RG 4	Hématopathies caused by benzene and all products containing it
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 34	Disorders caused by alkyl, aryl or alkylaryl phosphates, pyrophosphates and thiophosphates and other organophosphorus, anticholinesterase as well as anticholinesterase phosphoramides and heterocyclic carbamates
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

15.2. Évaluation de la sécurité chimique

Aucune évaluation chimique de sécurité n'a été effectuée.

Une évaluation de la sécurité chimique a été réalisée pour les substances suivantes de ce mélange:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts

RUBRIQUE 16: Autres informations

Abréviations et acronymes	
	ATE: estimation de toxicité aiguë
	CAS (Chemical Abstracts Service) number.
	CLP: Classification, étiquetage, emballage.
	CE50: concentration environnementale associée à une réponse de 50% de la population d'essai.
	Code catalogue européen des déchets (CED)
	LD50: Dose létale pour 50% de la population d'essai
	PBT: substances persistantes, bioaccumulables, toxiques
	STEL: à court terme de limites d'exposition
	TWA: Poids moyen
vPvB	Very Persistent and Very Bioaccumulative

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Sources des données	: European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . Informations sur le fabricant. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. RÈGLEMENT (CE) No 1272/2008 DU PARLEMENT EUROPÉEN ET DU CONSEIL du 16 décembre 2008 relatif à la classification, à l'étiquetage et à l'emballage des substances et des mélanges, modifiant et abrogeant les directives 67/548/CEE et 1999/45/CE et modifiant le règlement (CE) no 1907/2006.
Autres informations	: Aucun(e).

Texte intégral des phrases H et EUH	
Acute Tox. 3 (par inhalation : poussières, brouillard)	Toxicité aiguë (Inhalation:poussières,brouillard) Catégorie 3
Acute Tox. 3 (par inhalation)	Toxicité aiguë (par Inhalation), catégorie 3
Acute Tox. 3 (par voie cutanée)	Toxicité aiguë (par voie cutanée), catégorie 3
Acute Tox. 3 (par voie orale)	Toxicité aiguë (par voie orale), catégorie 3
Acute Tox. 4 (par inhalation : poussières, brouillard)	Toxicité aiguë (Inhalation:poussières,brouillard) Catégorie 4
Acute Tox. 4 (par inhalation)	Toxicité aiguë (par Inhalation), catégorie 4
Acute Tox. 4 (par voie cutanée)	Toxicité aiguë (par voie cutanée), catégorie 4
Acute Tox. 4 (par voie orale)	Toxicité aiguë (par voie orale), catégorie 4
Aquatic Acute 1	Dangereux pour le milieu aquatique – Danger aigu, catégorie 1
Aquatic Chronic 1	Dangereux pour le milieu aquatique – Danger chronique, catégorie 1
Aquatic Chronic 2	Dangereux pour le milieu aquatique – Danger chronique, catégorie 2
Aquatic Chronic 3	Dangereux pour le milieu aquatique – Danger chronique, catégorie 3
Aquatic Chronic 4	Dangereux pour le milieu aquatique – Danger chronique, catégorie 4
Asp. Tox. 1	Danger par aspiration, catégorie 1
Asp. Tox. Non classé	Danger par aspiration Non classé
Carc. 1A	Cancérogénicité, catégorie 1A
Carc. 2	Cancérogénicité, catégorie 2
Carc. Non classé	Cancérogénicité Non classé
Eye Dam. 1	Lésions oculaires graves/irritation oculaire, catégorie 1
Eye Dam./Irrit. Non classé	Lésions oculaires graves/irritation oculaire Non classé
Eye Irrit. 2	Lésions oculaires graves/irritation oculaire, catégorie 2
Flam. Liq. 2	Liquides inflammables, catégorie 2

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Texte intégral des phrases H et EUH	
Flam. Liq. 3	Liquides inflammables, catégorie 3
H225	Liquide et vapeurs très inflammables.
H226	Liquide et vapeurs inflammables.
H301	Toxique en cas d'ingestion.
H302	Nocif en cas d'ingestion.
H304	Peut être mortel en cas d'ingestion et de pénétration dans les voies respiratoires.
H311	Toxique par contact cutané.
H312	Nocif par contact cutané.
H314	Provoque de graves brûlures de la peau et de graves lésions des yeux.
H315	Provoque une irritation cutanée.
H317	Peut provoquer une allergie cutanée.
H318	Provoque de graves lésions des yeux.
H319	Provoque une sévère irritation des yeux.
H331	Toxique par inhalation.
H332	Nocif par inhalation.
H334	Peut provoquer des symptômes allergiques ou d'asthme ou des difficultés respiratoires par inhalation.
H335	Peut irriter les voies respiratoires.
H336	Peut provoquer somnolence ou vertiges.
H340	Peut induire des anomalies génétiques.
H350	Peut provoquer le cancer.
H351	Susceptible de provoquer le cancer.
H360F	Peut nuire à la fertilité.
H361	Susceptible de nuire à la fertilité ou au fœtus.
H361d	Susceptible de nuire au fœtus.
H372	Risque avéré d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
H373	Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
H400	Très toxique pour les organismes aquatiques.
H410	Très toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H411	Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H412	Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H413	Peut être nocif à long terme pour les organismes aquatiques.
Muta. 1B	Mutagénicité sur les cellules germinales, catégorie 1B
Muta. Non classé	Mutagénicité sur les cellules germinales Non classé
Repr. 1B	Toxicité pour la reproduction, catégorie 1B
Repr. 2	Toxicité pour la reproduction, catégorie 2

Lucas Synthetic SAE 5W-40 European Motor Oil, Lucas SAE 30 Break-In Oil, Lucas Semi-Synthetic SAE 10W-40 European Motor Oil, Lucas Synthetic SAE 5W-30 European Motor Oil, Lucas Semi-Synthetic SAE 5W-30 European Motor Oil, Lucas SAE 85W-140 Heavy Duty Gear Oil, Lucas SAE 80W-90 Heavy Duty Gear Oil, Lucas Synthetic SAE 15W-40 Magnum CJ-4, Lucas SAE 20W-50 Break-In Oil, Lucas Power Steering Fluid, Lucas Synthetic SAE 10W-60 European Motor Oil, Lucas Semi-Synthetic SAE 15W-40 European Motor Oil, Lucas Synthetic SAE 10W-30 European Motor Oil, Lucas Power Steering Fluid with Conditioners, L.O.P. Super Lube Semi-Synthetic 10w-40 Motor Oil, L.O.P. Super Lube Semi-Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-30 Motor Oil, L.O.P. Super Lube Fully Synthetic 5w-40 Motor Oil, Lucas SAE 75W-140 Synthetic Gear Oil, Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil, Lucas SAE 75W-90 Synthetic Gear Oil, Lucas Synthetic SAE 10W-40 Outboard Engine Oil, Lucas SAE 15W-40 Magnum CI-4/SM, Lucas Extreme Duty Outboard Engine Oil Synthetic SAE 10W-30, Anti-Squawk/Anti-Shudder Trans & Diff Additive, Lucas Synthetic SAE 20W-50 European Motor Oil

Fiche de données de sécurité

conforme au Règlement (CE) N° 1907/2006 (REACH) tel que modifié par le Règlement (UE) 2020/878

Texte intégral des phrases H et EUH	
Resp. Sens. 1	Sensibilisation respiratoire, catégorie 1
Skin Corr. 1B	Corrosif/irritant pour la peau, catégorie 1, sous-catégorie 1B
Skin Corr. 1C	Corrosif/irritant pour la peau, catégorie 1, sous-catégorie 1C
Skin Corr./Irrit. Non classé	Corrosif/irritant pour la peau Non classé
Skin Irrit. 2	Corrosif/irritant pour la peau, catégorie 2
Skin Sens. 1	Sensibilisation cutanée, catégorie 1
STOT RE 1	Toxicité spécifique pour certains organes cibles – Exposition répétée, catégorie 1
STOT RE 2	Toxicité spécifique pour certains organes cibles – Exposition répétée, catégorie 2
STOT SE 3	Toxicité spécifique pour certains organes cibles – Exposition unique, catégorie 3, Irritation des voies respiratoires

Classification et procédure utilisée pour établir la classification des mélanges conformément au règlement (CE) 1272/2008 [CLP]		
Skin Corr./Irrit. Non classé		Jugement d'experts
Eye Dam./Irrit. Non classé		Jugement d'experts
Asp. Tox. Non classé		Jugement d'experts
Aquatic Chronic 3	H412	Méthode de calcul

Ces informations sont basées sur nos connaissances actuelles et décrivent le produit pour les seuls besoins de la santé, de la sécurité et de l'environnement. Elles ne devraient donc pas être interprétées comme garantissant une quelconque propriété spécifique du produit