

# Lucas Oil Synthetic 10W-40 Engine Oil Lucas Oil Products UK (IE)

Part Number: 47052, 47053, 47054, 47055

Version No: 1.1

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Issue Date: **03/04/2024** Print Date: **07/04/2024** S.REACH.IRL.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

### 1.1. Product Identifier

Product name	ucas Oil Synthetic 10W-40 Engine Oil	
Chemical Name	Not Applicable	
Synonyms	lixture	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Category Consumer	PC24 Lubricants, greases, release products
Relevant identified uses Use according to manufacturer's directions.	
Uses advised against No specific uses advised against are identified.	

### 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lucas Oil Products UK (IE)	Lucas Oil Products Europe Ltd
Address	Unit 4 Cunliffe Drive Llangefni Industrial Estate LL77 7JA Llangefni Great Britain	Block 3 Harcourt Centre Dublin 2 Ireland
Telephone	+44 (0) 1248 723 666	+44 344 225 5400
Fax	Not Available	Not Available
Website	www.lucasoil.co.uk	www.lucasoil.eu.com
Email	Info@LucasOil.co.uk	info@lucasoil.eu.com

### 1.4. Emergency telephone number

Association / Organisation	National Poisons Information Centre Beaumont Hospital	ChemTel
Emergency telephone numbers	+353 1 809 2166	1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)
Other emergency telephone numbers	Not Available	+1-813-248-0585 (International)

### **SECTION 2 Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008	Not Applicable
[CLP] and amendments [1]	

# 2.2. Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

# Hazard statement(s)

Not Applicable

### Supplementary statement(s)

Not Applicable

### Precautionary statement(s) Prevention

Not Applicable

Page 2 of 11

Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

### Precautionary statement(s) Response

Not Applicable

Version No: 1.1

### Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

Not Applicable

 $Material\ contains\ zinc\ bis (1,3-dimethylbutyl) dithiophosphate,\ zinc\ bis (2-ethylhexyl) dithiophosphate.$ 

### 2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

### **SECTION 3 Composition / information on ingredients**

#### 3.1.Substances

See 'Composition on ingredients' in Section 3.2

### 3.2.Mixtures

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M- Factor	Nanoform Particle Characteristics
1. 2215-35-2* 2.218-679-9 3.Not Available 4.Not Available	0.2-1	zinc bis(1,3- dimethylbutyl)dithiophosphate	Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 2; H315, H318, H411 [1]	Not Available	Not Available
1. 4259-15-8* 2.224-235-5 3.Not Available 4.Not Available	0.05- 0.25	zinc bis(2- ethylhexyl)dithiophosphate	Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 2; H318, H411 <sup>[1]</sup>	Not Available	Not Available
Legend:			rawn from Regulation (EU) No 1272/2008 - Annex VI; 3. aving endocrine disrupting properties	Classification	drawn from C&L * EU

### **SECTION 4 First aid measures**

# 4.1. Description of first aid measures

Eye Contact  If this product comes in contact with eyes:  Wash out immediately with water.  If irritation continues, seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.		
Skin Contact	If skin or hair contact occurs:  Contact  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.	
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>	
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>	

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 Firefighting measures**

### 5.1. Extinguishing media

- ▶ Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None ki	nown.
------------------------------	-------


# 5.3. Advice for firefighters

# Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.

# Page 3 of 11 Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: 03/04/2024 Print Date: 07/04/2024



### **SECTION 6 Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

Version No: 1.1

### 6.2. Environmental precautions

See section 12

### 6.3. Methods and material for containment and cleaning up

► Remove all ignition sources.	
► Clean up all spills immediately.	
Avoid breathing vapours and contact with skin and eyes.	
Minor Spills ▶ Control personal contact with the substance, by using protective equipment.	
▶ Contain and absorb spill with sand, earth, inert material or vermiculite.	
▶ Wipe up.	
▶ Place in a suitable, labelled container for waste disposal.	
Moderate hazard.	
▶ Clear area of personnel and move upwind.	
▶ Alert Fire Brigade and tell them location and nature of hazard.	
▶ Wear breathing apparatus plus protective gloves.	
Prevent, by any means available, spillage from entering drains or water course.	
▶ No smoking, naked lights or ignition sources.	
Maior Critta	
Major Spills  Stop leak if safe to do so.	
▶ Contain spill with sand, earth or vermiculite.	
▶ Collect recoverable product into labelled containers for recycling.	
▶ Absorb remaining product with sand, earth or vermiculite.	
▶ Collect solid residues and seal in labelled drums for disposal.	
▶ Wash area and prevent runoff into drains.	
▶ If contamination of drains or waterways occurs, advise emergency services.	

### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

7.1. Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>Avoid smoking, naked lights or ignition sources.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul>
Fire and explosion protection	See section 5
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>

# 7.2. Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed.  None known

▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks.

Page 4 of 11

Version No: 1.1

### Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

### 7.3. Specific end use(s)

See section 1.2

### SECTION 8 Exposure controls / personal protection

### 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
zinc bis(1,3- dimethylbutyl)dithiophosphate	Dermal 12.2 mg/kg bw/day (Systemic, Chronic) Inhalation 8.6 mg/m³ (Systemic, Chronic) Dermal 6.1 mg/kg bw/day (Systemic, Chronic) * Inhalation 2.13 mg/m³ (Systemic, Chronic) * Oral 0.24 mg/kg bw/day (Systemic, Chronic) *	4 μg/L (Water (Fresh)) 45 μg/L (Water - Intermittent release) 4.6 μg/L (Water (Marine)) 0.074 mg/kg sediment dw (Sediment (Fresh Water)) 0.007 mg/kg sediment dw (Sediment (Marine)) 0.01 mg/kg soil dw (Soil) 100 mg/L (STP) 10.67 mg/kg food (Oral)
zinc bis(2- ethylhexyl)dithiophosphate	Dermal 9.6 mg/kg bw/day (Systemic, Chronic) Inhalation 6.6 mg/m³ (Systemic, Chronic) Dermal 4.8 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.67 mg/m³ (Systemic, Chronic) * Oral 0.19 mg/kg bw/day (Systemic, Chronic) *	4 μg/L (Water (Fresh)) 44 μg/L (Water - Intermittent release) 4.6 μg/L (Water (Marine)) 0.322 mg/kg sediment dw (Sediment (Fresh Water)) 0.032 mg/kg sediment dw (Sediment (Marine)) 0.062 mg/kg soil dw (Soil) 3.8 mg/L (STP) 8.33 mg/kg food (Oral)

<sup>\*</sup> Values for General Population

### Occupational Exposure Limits (OEL)

TEEL-1

### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

TEEL-2

### Not Applicable

Ingredient

### Emergency Limits

Lucas Oil Synthetic 10W-40 Engine Oil	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
zinc bis(1,3- dimethylbutyl)dithiophosphate	Not Available		Not Available	
zinc bis(2- ethylhexyl)dithiophosphate	Not Available		Not Available	

### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
zinc bis(1,3- dimethylbutyl)dithiophosphate	E	≤ 0.01 mg/m³	
zinc bis(2- ethylhexyl)dithiophosphate	С	> 0.1 to ≤ milligrams per cubic meter of air (mg/m³)	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

### 8.2. Exposure controls

# 8.2.1. Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

TEEL-3

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in

Page 5 of 11

Version No: 1.1

### Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

# 8.2.2. Individual protection measures, such as personal protective equipment







# Eye and face protection

### "Safety glasses with side shields

- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]"

### Skin protection

Hands/feet protection

### See Hand protection below

▶ Wear general protective gloves, eg. light weight rubber gloves.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- $\cdot$  glove thickness and
- · dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

· Contaminated gloves should be replaced.

- As defined in ASTM F-739-96 in any application, gloves are rated as:
- · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Part Number: 47052, 47053, 47054, 47055

# Page 6 of 11 Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

Body protection	See Other protection below	
Other protection	No special equipment needed when handling small quantities.  OTHERWISE:  Overalls.  Barrier cream.  Eyewash unit.	

### 8.2.3. Environmental exposure controls

See section 12

Version No: 1.1

# **SECTION 9 Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance	Amber Clear and Bright Oil		
Physical state	Liquid	Relative density (Water = 1)	0.854
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-39	Viscosity (cSt)	86.4 @ 40°C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>200	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

# 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2	
10.2. Chemical stability	roduct is considered stable and hazardous polymerisation will not occur.	
10.3. Possibility of hazardous reactions	See section 7.2	
10.4. Conditions to avoid	See section 7.2	
10.5. Incompatible materials	See section 7.2	
10.6. Hazardous decomposition products	See section 5.3	

# **SECTION 11 Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Page 7 of 11

Version No: 1.1

### Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

Lucas Oil Synthetic 10W-40	TOXICITY	IRRITATION
Engine Oil	Not Available	Not Available
	TOXICITY	IRRITATION
zinc bis(1,3-	Dermal (rabbit) LD50: >25000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
dimethylbutyl)dithiophosphate	Inhalation (Rat) LC50: >0.5 mg/l4h <sup>[1]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>
	Oral (Rat) LD50: >2000<5000 mg/kg <sup>[1]</sup>	
	TOXICITY	IRRITATION
zinc bis(2- ethylhexyl)dithiophosphate	Dermal (rabbit) LD50: >5000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
	Oral (Rat) LD50: >2000<5000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Legend:	Nature obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwing specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

zinc bis(1,3dimethylbutyl)dithiophosphate & zinc bis(2ethylhexyl)dithiophosphate No significant acute toxicological data identified in literature search.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Dithiophosphate alkyl esters is corrosive and toxic to the tissues on skin or oral exposure depending on its concentration. Symptoms included diarrhoea, skin and gastrointestinal irritation, lethargy, reduced food intake, staining about the nose and eye; occasionally, there was drooping of the eyelid, hair standing up, inco-ordination and salivation. Toxicity is reduced following inhalation (due to vapour pressure and high viscosity). It may produce reproductive, developmental and genetic toxicity on experimental animals, but no substantive data is available to establish effect on humans.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

💢 – Data either not available or does not fill the criteria for classification

— Data available to make classification

### 11.2 Information on other hazards

### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

### 12.1. Toxicity

Lucas Oil Synthetic 10W-40 Engine Oil	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available Not Available		Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
zinc bis(1,3- dimethylbutyl)dithiophosphate	EC50	48h	Crustacea	46mg/l	1
	EC50	96h	Algae or other aquatic plants  1- 5mg/l		1
	LC50	96h	Fish	46mg/l	2
	NOEC(ECx)	48h	Crustacea	<1mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	11.5mg/l	1
zinc bis(2- ethylhexyl)dithiophosphate	EC50	96h	Algae or other aquatic plants	1-5mg/l	1
	NOEC(ECx)	48h	Crustacea	<1mg/l	1
	LC50	96h	Fish	46mg/l	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data No Data available for all ingredients

Part Number: 47052, 47053, 47054, 47055

# Page 8 of 11 Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: 03/04/2024 Print Date: 07/04/2024

Ingredient	Persistence: Water/Soil	Persistence: Air			
	No Data available for all ingredients	No Data available for all ingredients			
12.3. Bioaccumulative potential					
Ingredient	Bioaccumulation				

# 12.4. Mobility in soil

Version No: 1.1

Ingredient	Mobility	
	No Data available for all ingredients	

#### 12.5. Results of PBT and vPvB assessment

	Р	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT	X	×	X
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

### **SECTION 13 Disposal considerations**

### 13.1. Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- ▶ Reuse
- Recycling
- ▶ Disposal (if all else fails)

# Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Waste treatment options

Not Available

Sewage disposal options Not Available

### **SECTION 14 Transport information**

### Labels Required

Marine Pollutant	NO

### d transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Land transport (ADR): NOT R	Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS			
14.1. UN number or ID number	Not Applicable			
14.2. UN proper shipping name	Not Applicable			
14.3. Transport hazard class(es)	Class Not Applicable Subsidiary Hazard Not Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Hazard identification (Kemler)  Not Applicable  Classification code  Not Applicable			

Version No: 1.1

Page 9 of 11

Lucas Oil Synthetic 10W-40 Engine Oil

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

Hazard Label No	ot Applicable
Special provisions No	ot Applicable
Limited quantity No	ot Applicable
Tunnel Restriction Code No	ot Applicable

### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable			
14.2. UN proper shipping name	Not Applicable			
	ICAO/IATA Class Not Applicable			
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	ICAO / IATA Subsidiary Hazard Not Applicable		
0.000(00)	ERG Code	Not Applicable		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		Not Applicable	
	Cargo Only Maximum Qty / Pack		Not Applicable	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		Not Applicable	
4501	Passenger and Cargo Maximum Qty / Pack		Not Applicable	
	Passenger and Cargo Limited Quantity Packing Instructions		Not Applicable	
	Passenger and Cargo Limited Ma	aximum Qty / Pack	Not Applicable	

## Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard	IMDG Class	Not Applicable
class(es)	IMDG Subsidiary Ha	azard Not Applicable
14.4. Packing group	Not Applicable	
14.5 Environmental hazard	Not Applicable	
	EMS Number	Not Applicable
14.6. Special precautions for user	Special provisions	Not Applicable
	Limited Quantities	Not Applicable

# Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	Not Applicable Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	Classification code Special provisions	Not Applicable  Not Applicable	
14.6. Special precautions for user	Limited quantity	Not Applicable	
455	Equipment required	Not Applicable	
	Fire cones number	Not Applicable	

# 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
zinc bis(1,3- dimethylbutyl)dithiophosphate	Not Available
zinc bis(2- ethylhexyl)dithiophosphate	Not Available

Lucas Oil Synthetic 10W-40 Engine Oil

Page 10 of 11 Issue Date: 03/04/2024 Version No: 1.1 Print Date: 07/04/2024

### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
zinc bis(1,3- dimethylbutyl)dithiophosphate	Not Available
zinc bis(2- ethylhexyl)dithiophosphate	Not Available

### **SECTION 15 Regulatory information**

### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

### zinc bis(1,3-dimethylbutyl)dithiophosphate is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

### zinc bis(2-ethylhexyl)dithiophosphate is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

# **Additional Regulatory Information**

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

### Information according to 2012/18/EU (Seveso III):

_	
Seveso Category	Not Available

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (zinc bis(1,3-dimethylbutyl)dithiophosphate; zinc bis(2-ethylhexyl)dithiophosphate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (zinc bis(1,3-dimethylbutyl)dithiophosphate; zinc bis(2-ethylhexyl)dithiophosphate)
Vietnam - NCI	Yes
Russia - FBEPH	No (zinc bis(1,3-dimethylbutyl)dithiophosphate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### **SECTION 16 Other information**

Revision Date	03/04/2024
Initial Date	03/04/2024

### Full text Risk and Hazard codes

H315	Causes skin irritation.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

Page 11 of 11

Version No: 1.1

Issue Date: **03/04/2024**Print Date: **07/04/2024** 

Lucas Oil Synthetic 10W-40 Engine Oil Print Date: 07/04/2024

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ► KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ► NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.