

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil Lucas Oil Products UK (MT)

Part Number: 47012, 47013, 47014, 47015

Version No: 1.2

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Issue Date: **03/04/2024** Print Date: **05/04/2024** S.REACH.MLT.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	ucas Oil Synthetic 0W-30 C2 ECO Engine Oil	
Chemical Name	Not Applicable	
Synonyms	Mixture	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Category Consumer	PC24 Lubricants, greases, release products	
Relevant identified uses	Jse according to manufacturer's directions.	
Uses advised against	No specific uses advised against are identified.	

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lucas Oil Products UK (MT)	Lucas Oil Products Europe Ltd
Address	Unit 4 Cunliffe Drive Llangefni Industrial Estate LL77 7JA Llangefni Great Britain	Block 3 Harcourt Centre Dublin 2 Ireland
Telephone	+44 (0) 1248 723 666	+44 344 225 5400
Fax	Not Available	Not Available
Website	www.lucasoil.co.uk	www.lucasoil.eu.com
Email	Info@LucasOil.co.uk	info@lucasoil.eu.com

1.4. Emergency telephone number

Association / Organisation	Medicines & Poisons Info Office ChemTel	
Emergency telephone numbers	+356 2545 6508	1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)
Other emergency telephone numbers	Not Available	+1-813-248-0585 (International)

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008	Not Applicable
[CLP] and amendments [1]	

2.2. Label elements

Hazard pictogram(s)	Not Applicable
	<u>''</u>
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Supplementary statement(s)

ouppiementary statement(s)	
EUH208	Contains molybdenum alkylthiocarbamide complex. May produce an allergic reaction.

Page 2 of 11

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

Not Applicable

Version No: 1.2

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

Material contains molybdenum alkylthiocarbamide complex.

2.3. Other hazards

Possible skin sensitizer*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M- Factor	Nanoform Particle Characteristics
1. 36878-20-3* 2.253-249-4 3.Not Available 4.Not Available	1-5	nonylated diphenylamines	Hazardous to the Aquatic Environment Long-Term Hazard Category 4; H413 ^[1]	Not Available	Not Available
Not Available Not Available Not Available Not Available Anot Available	<1	molybdenum alkylthiocarbamide complex	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1; H315, H317, H318 ^[1]	Not Available	Not Available
Legend:		•	tion drawn from Regulation (EU) No 1272/2008 - Annex VI, d as having endocrine disrupting properties	3. Classification	n drawn from C&L * EU

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ▶ Foam.
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.
- ▶ Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

5.3. Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

Part Number: 47012, 47013, 47014, 47015

Page 3 of 11

Version No: 1.2

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

	 Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes. May emit acrid smoke. Mists containing combustible materials may be explosive. May emit corrosive fumes.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

v.o. Methods and material for Containment and Geaning up		
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. 	
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.	

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Fire and explosion protection	► DO NOT allow clothing wet with material to stay in contact with skin See section 5
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- ▶ Packaging as recommended by manufacturer.

Page 4 of 11 Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: 03/04/2024 Print Date: 05/04/2024

▶ Check all containers are clearly labelled and free from leaks. Storage incompatibility None known Hazard categories in accordance with Regulation Not Available (EC) No 2012/18/EU (Seveso **Qualifying quantity (tonnes)** of dangerous substances as Not Available referred to in Article 3(10) for the application of

7.3. Specific end use(s)

See section 1.2

Version No: 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
nonylated diphenylamines	Not Available	Not Available
molybdenum alkylthiocarbamide complex	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
molybdenum alkylthiocarbamide complex	E	≤ 0.01 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into adverse health outcomes associated with exposure. The output of this p to a range of exposure concentrations that are expected to protect work	process is an occupational exposure band (OEB), which corresponds

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Part Number: 47012, 47013, 47014, 47015 Page 5 of 11 Issue Date: 03/04/2024 Print Date: 05/04/2024

Version No: 1.2

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Lower end of the range Upper end of the range 1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of high toxicity 2: Contaminants of low toxicity or of nuisance value only 3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

8.2.2. Individual protection measures, such as personal protective equipment







Eve and face protection

Safety glasses with side shields.

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 591.

Skin protection

See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroved.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact
- · chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended

Body protection

Hands/feet protection

See Other protection below

Other protection

- Overalls. P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

8.2.3. Environmental exposure controls

Part Number: **47012, 47013, 47014, 47015** Version No: **1.2**

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Amber Clear and Bright Oil		
Physical state	Liquid	Relative density (Water = 1)	0.841
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-45	Viscosity (cSt)	57.4 @ 40°C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	216	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1. Information on hazard cla	sses as defined in Regulation (EC) No 1272/2008				
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.				
Ingestion	The material has NOT been classified by EC Directives of corroborating animal or human evidence.	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.			
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.				
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).				
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.				
Lucas Oil Synthetic 0W-30 C2	TOXICITY	IRRITATION			
ECO Engine Oil	Not Available	Not Available			
	TOXICITY	IRRITATION			
nonylated diphenylamines Oral (Rat) LD50; >5000 mg/kg * ^[2] Eve: no adverse effect observed (not irritating) ^[1]					

Skin: no adverse effect observed (not irritating) $^{[1]}$

Version No: 1.2

Page 7 of 11 Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

	TOXICITY	IRRITATION
molybdenum alkylthiocarbamide complex	dermal (rat) LD50: >2000 mg/kg *[2]	Not Available
	Oral (Rat) LD50: >2000 mg/kg * ^[2]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwis specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

nonylated diphenylamines

Heating of substituted diphenylamines may generate vapours which can irritate the eyes and airways. Drying of skin and mucous membranes leading to irritation may occur with prolonged or repeated contact. Overexposure may cause skin and airway irritation with dizziness and flu-like symptoms. All show a slight to very low order of toxicity following oral or topical administration. There is very low potential to cause gene mutations.

Toxicity data for the base-oil containing material. The repeat-dose oral toxicity data only found effects in the top dose group administered

molybdenum alkylthiocarbamide complex

1,000 mg/kg bw/day, which indicates the substance is absorbed through the gastrointestinal tract, but possibly only to a very limited extent. The absence of effects in the repeat-dose dermal toxicity study indicates that if any dermal absorption occurs at all, it occurs at a lower rate than oral absorption. The high partition coefficient indicates that any molecules that are absorbed will partition preferentially to lipid-rich tissues, and this is supported by the reproduction/developmental toxicity screening study which reported clinical observations suggestive of Central Nervous System toxicity at the top dose (1,000 mg/kg bw/day). The available environmental degradation data indicate that the substance is not readily biodegraded. If mammalian metabolism is similarly limited, this would suggest the potential for bioaccumulation. However, the true bioaccumulation potential is likely to be low, due to the limited absorption potential. Sensitisation: The substance was tested in a Guinea-Pig Maximisation Test, which employs intradermal injection and use of adjuvant. Upon challenge application, six of the 20 animals treated with the test substance showed slight and patchy erythema; the control animals showed no response to challenge. Therefore the substance was concluded to be a weak sensitiser in this test. In accordance with CLP, when an adjuvant type guinea pig test is used, a response of at least 30% of the animals (equivalent to six out of 20 animals) is considered as positive. Therefore, the substance is classified as a skin sensitiser (Category 1) under CLP. There are no human or suitable animal data regarding the respiratory sensitisation potential of the substance. As the substance is only a borderline skin sensitiser according to CLP criteria, and as the potential for inhalation exposure to the substance will be negligible, no classification is proposed for respiratory sensitisation. Repeat dose toxicity: No treatmentrelated systemic toxicity was seen in the 28-day dermal toxicity study of a substance structurally and chemically similar to EC 457-320-2, and the NOAEL was concluded to be 670 mg/kg bw/day. No hazard classifications are required based on this study. The two repeat-dose oral studies available (28-day toxicity study and a reproduction/developmental toxicity screening study) identified no consistent identifiable treatment-related toxic effects at dose levels that might necessitate classification for Specific Target Organ Toxicity (STOT-RE). Consequently, in accordance with CLP, no hazard classifications are proposed. Genetic toxicity The substance showed no evidence of mutagenic potential in an Ames test. A second structurally and chemically similar substance showed no evidence of genotoxic potential in an in vitro chromosome aberraton study and an in vivo mouse micronucleus study Toxicity to Reproduction: The NOAEL for general parental toxicity was therefore concluded to be 300 mg/kg bw/day. However, there were no effects on any reproductive or neonatal parameters assessed, and the NOAEL both for reproduction toxicity and developmental toxicity were concluded to be 1,000 mg/kg bw/day. Therefore, no classification is required. * REACh Dossier

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil & molybdenum alkylthiocarbamide complex

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

X - Data either not available or does not fill the criteria for classification

– Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
nonylated diphenylamines	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	733mg/l	Not Available
	EC50	96h	Algae or other aquatic plants	870mg/l	2
	EC50	72h	Algae or other aquatic plants	600mg/l	2

Version No: 1.2

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Page 8 of 11 Issue Date: 03/04/2024 Print Date: 05/04/2024

	NOEC(ECx)	96h	Crustacea	<10mg/l	1
	LC50	96h	Fish	>10000mg/l	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
molybdenum alkylthiocarbamide complex	Not Available	Not Available	Not Available	Not Available	Not Available

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	P	В	Т	
Relevant available data	Not Available	Not Available	Not Available	
PBT	X	×	×	
PBT vPvB	×	x	×	
PBT Criteria fulfilled?			No	
vPvB			No	

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling

Not Available

Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Sewage disposal options Not Available **SECTION 14 Transport information**

Waste treatment options

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

Labels Required

Version No: 1.2

Labels Required	1				
Marine Pollutant	NO				
Land transport (ADR): NOT RE	GULATED FOR TRANS	SPORT OI	F DANGEROUS (GOODS	
14.1. UN number or ID number	Not Applicable				
14.2. UN proper shipping name	Not Applicable				
14.3. Transport hazard	Class	Class Not Applicable			
class(es)	Subsidiary Hazard	Not Applic	cable		
14.4. Packing group	Not Applicable				
14.5. Environmental hazard	Not Applicable				
	Hazard identification (Kemler)		Not Applicable		
	Classification code		Not Applicable		
14.6. Special precautions for	Hazard Label		Not Applicable		
user	Special provisions		Not Applicable		
	Limited quantity		Not Applicable		
	Tunnel Restriction Code		Not Applicable		
Air transport (ICAO-IATA / DGF	R): NOT REGULATED F	OR TRAN	SPORT OF DANG	GEROUS GOODS	
14.1. UN number	Not Applicable				
14.2. UN proper shipping name	Not Applicable	Not Applicable			
	ICAO/IATA Class		Not Applicable		
14.3. Transport hazard class(es)	ICAO / IATA Subsidia	ry Hazard	Not Applicable		
Ciass(es)	ERG Code		Not Applicable		

14.6. Special precautions for user

14.4. Packing group14.5. Environmental hazard

Not Applicable	
Not Applicable	
Special provisions	Not Applicable
Cargo Only Packing Instructions	Not Applicable
Cargo Only Maximum Qty / Pack	Not Applicable
Passenger and Cargo Packing Instructions	Not Applicable
Passenger and Cargo Maximum Qty / Pack	Not Applicable
Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable			
14.2. UN proper shipping name	Not Applicable			
14.3. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subsidiary Hazard Not Applicable			
14.4. Packing group	Not Applicable			
14.5 Environmental hazard	Not Applicable			
14.6. Special precautions for user	EMS Number Not Applicable Special provisions Not Applicable Limited Quantities Not Applicable			

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable
14.2. UN proper shipping name	Not Applicable
14.3. Transport hazard class(es)	Not Applicable Not Applicable
14.4. Packing group	Not Applicable
14.5. Environmental hazard	Not Applicable

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: **03/04/2024**Print Date: **05/04/2024**

14.6. Special precautions for user

Classification code Not Applicable
Special provisions Not Applicable
Limited quantity Not Applicable
Equipment required Not Applicable
Fire cones number Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Version No: 1.2

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
nonylated diphenylamines	Not Available
molybdenum alkylthiocarbamide complex	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
nonylated diphenylamines	Not Available
molybdenum alkylthiocarbamide complex	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

nonylated diphenylamines is found on the following regulatory lists

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

molybdenum alkylthiocarbamide complex is found on the following regulatory lists

Not Applicable

Additional Regulatory Information

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (nonylated diphenylamines)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (nonylated diphenylamines)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

Page 11 of 11

Lucas Oil Synthetic 0W-30 C2 ECO Engine Oil

Issue Date: 03/04/2024 Print Date: 05/04/2024

SECTION 16 Other information

Version No: 1.2

Revision Date	03/04/2024
Initial Date	03/04/2024

Full text Risk and Hazard codes

H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H413	May cause long lasting harmful effects to aquatic life.	

SDS Version Summary

Version	Date of Update	Sections Updated
0.2	03/04/2024	Composition / information on ingredients - Ingredients

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
, EUH208	Calculation method

Powered by AuthorITe, from Chemwatch.