

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil Lucas Oil Products UK (GB)

Part Number: 47024, 47025, 47026, 47027

Version No: 3.3

Safety data sheet according to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Issue Date: 22/07/2024 Print Date: 22/07/2024 S.REACH.GB.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil	
Chemical Name	Not Applicable	
Synonyms	Mixture	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Category Consumer	PC24 Lubricants, greases, release products	
Relevant identified uses	Use according to manufacturer's directions.	
Uses advised against	No specific uses advised against are identified.	

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lucas Oil Products UK (GB)	Lucas Oil Products Europe Ltd
Address	Unit 4 Cunliffe Drive Llangefni Industrial Estate LL77 7JA Llangefni Great Britain	Block 3 Harcourt Centre Dublin 2 Ireland
Telephone	+44 (0) 1248 723 666	+44 344 225 5400
Fax	Not Available	Not Available
Website	www.lucasoil.co.uk	www.lucasoil.eu.com
Email	Info@LucasOil.co.uk	info@lucasoil.eu.com

1.4. Emergency telephone number

Association / Organisation	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	ChemTel
Emergency telephone numbers	020 7188 7188	1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)
Other emergency telephone numbers	Not Available	+1-813-248-0585 (International)

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classified according to GB-	
CLP Regulation, UK SI	Niet Augliecht
2019/720 and UK SI	Not Applicable
2020/1567 ^[1]	

2.2. Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Supplementary statement(s)

Version No: 3.3

Page 2 of 15 Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Print Date: 22/07/2024

EUH210 Safety data sheet available on request.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

Material contains lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)*, lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346), paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346), paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*.

2.3. Other hazards

lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	SCL / M- Factor	Nanoform Particle Characteristics
1. 72623-86-0.* 2.276-737-9 3.649-482-00-X 4.Not Available	10-50	lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	Aspiration Hazard Category 1; H304 ^[1]	Not Available Acute M factor: Not Available Chronic M factor: Not Available	Not Available
1. 72623-87-1* 2.276-738-4 3.649-483-00-5 4.Not Available	<10	lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346)	Aspiration Hazard Category 1; H304 ^[1]	Not Available Acute M factor: Not Available Chronic M factor: Not Available	Not Available
1. 64742-56-9.* 2.265-159-2 3.649-469-00-9 4.Not Available	<10	paraffinic distillate, light, solvent- dewaxed (severe) (DMSO <3% w/w by IP 346)	Aspiration Hazard Category 1; H304 ^[1]	Not Available Acute M factor: Not Available Chronic M factor: Not Available	Not Available
1. 64742-65-0.* 2.265-169-7 3.649-474-00-6 4.Not Available	<10	paraffinic distillate, heavy, solvent- dewaxed (severe) (DMSO <3% w/w by IP 346)*	Aspiration Hazard Category 1; H304 ^[1]	Not Available Acute M factor: Not Available Chronic M factor: Not Available	Not Available
1. 64742-70-7.* 2.265-174-4 3.649-477-00-2	<10	paraffinic distillate, heavy, solvent- dewaxed (severe). (DMSO <3%	Aspiration Hazard Category 1; H304 [1]	Not Available	Not Available

Version No: 3.3

Page 3 of 15

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	SCL / M- Factor	Nanoform Particle Characteristics
4.Not Available		<u>w/w by IP 346)</u>		Acute M factor: Not Available Chronic M factor: Not Available	
1. 1190625-94-5* 2.Not Available 3.Not Available 4.Not Available	<1	(C14-16-18)alkylphenol	Sensitisation (Skin) Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2; H317, H373 ^[1]	Not Available Acute M factor: Not Available Chronic M factor: Not Available	Not Available
Legend:	1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties				

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
5.3. Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes. May emit acrid smoke. Mists containing combustible materials may be explosive. May emit poisonous fumes.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

Issue Date: 22/07/2024

Print Date: 22/07/2024

Page 4 of 15

Version No: 3.3

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known
Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Page **5** of **15** Version No: 3.3 Print Date: 22/07/2024

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
lubricating oils, petroleum C15- 30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
lubricating oils, petroleum C20- 50, hydrotreated neutral (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
(C14-16-18)alkylphenol	Dermal 0.3 mg/kg bw/day (Systemic, Chronic) Inhalation 1.17 mg/m³ (Systemic, Chronic)	0.1 mg/L (Water (Fresh)) 1 mg/L (Water - Intermittent release) 0.01 mg/L (Water (Marine)) 4266.16 mg/kg sediment dw (Sediment (Fresh Water)) 426.62 mg/kg sediment dw (Sediment (Marine)) 852.58 mg/kg soil dw (Soil) 100 mg/L (STP) 3.3 mg/kg food (Oral)

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
lubricating oils, petroleum C15- 30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	140 mg/m3	1,500 mg/m3	8,900 mg/m3
lubricating oils, petroleum C20- 50, hydrotreated neutral (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3

Ingredient	Original IDLH	Revised IDLH
lubricating oils, petroleum C15- 30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	2,500 mg/m3	Not Available
lubricating oils, petroleum C20- 50, hydrotreated neutral (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	2,500 mg/m3	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe).	2,500 mg/m3	Not Available

Version No: 3.3

Page 6 of 15 Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Print Date: 22/07/2024

Ingredient	Original IDLH	Revised IDLH
(DMSO <3% w/w by IP 346)		
(C14-16-18)alkylphenol	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
(C14-16-18)alkylphenol	E	≤ 0.01 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)

8.2.1. Appropriate engineering controls

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

8.2.2. Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Version No: **3.3**

Page 7 of 15 Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374. AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber **Body protection** See Other protection below Overalls.

8.2.3. Environmental exposure controls

Other protection

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

P.V.C apron.

Barrier cream.Skin cleansing cream.Eye wash unit.

Appearance	Clear and Bright Pale Brown Oil		
Physical state	Liquid	Relative density (Water = 1)	0.848
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-42	Viscosity (cSt)	69 @ 40°C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>200	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2

Page 8 of 15

Version No: 3.3

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 		
10.3. Possibility of hazardous reactions	See section 7.2		
10.4. Conditions to avoid	See section 7.2		
10.5. Incompatible materials	See section 7.2		
10.6. Hazardous decomposition products	See section 5.3		

SECTION 11 Toxicological information

11.1.	Information	on	toxicologica	l effects
-------	-------------	----	--------------	-----------

1.1. Information on toxicologi					
Inhaled	· · · · · · · · · · · · · · · · · · ·	fects or irritation of the respiratory tract (as classified by EC Directives using animal hat exposure be kept to a minimum and that suitable control measures be used in a			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.				
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.				
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).				
Chronic	Repeated or long-term occupational exposure is likely to	produce cumulative health effects involving organs or biochemical systems.			
Lucas Oil Synthetic 5W-30 C3	TOXICITY	IRRITATION			
ECO Engine Oil	Not Available	Not Available			
	TOXICITY	IRRITATION			
lubricating oils, petroleum C15-30 hydrotreated neutral	Oral (Rat) LD50: >5000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]			
(DMSO <3% w/w by IP 346)*		Skin: no adverse effect observed (not irritating) ^[1]			
lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346)	TOXICITY	IRRITATION			
	Oral (Rat) LD50: >5000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]			
		Skin: no adverse effect observed (not irritating) ^[1]			
	TOXICITY	IRRITATION			
paraffinic distillate, light, solvent-dewaxed (severe)	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]			
(DMSO <3% w/w by IP 346)	Inhalation (Rat) LC50: 2.18 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]			
	Oral (Rat) LD50: >5000 mg/kg ^[2]				
	TOXICITY	IRRITATION			
paraffinic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]			
solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	Inhalation (Rat) LC50: 2.18 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]			
	Oral (Rat) LD50: >5000 mg/kg ^[2]				
	TOXICITY	IRRITATION			
paraffinic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]			
solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	Inhalation (Rat) LC50: 2.18 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]			
	Oral (Rat) LD50: >5000 mg/kg ^[1]				
	TOXICITY	IRRITATION			
(C14-16-18)alkylphenol	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]			
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) l^{11}			
Legend:		ances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise			
	specified data extracted from RTECS - Register of Toxic	ETTECT OF CHEMICAL SUBSTANCES			

lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346) For unrefined and mildly refined distillate base oils:

Acute toxicity: Animal testing showed high semilethal doses of >5000 mg/kg body weight and >2 g/kg body weight for exposure by swallowing or skin contact, respectively. The same material was also reported to be moderately irritating to skin, while not being sensitizing.

Page 9 of 15

Version No: 3.3

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Print Date: 22/07/2024

Repeat dose toxicity: Animal testing showed that repeat dose toxicity was mild to moderate to the skin. Reproductive / developmental toxicity: No studies on developmental toxicity or reproduction are available. Animal testing shows that high doses may reduce the body weight of both the mother and the foetus, and increase the rate of soft tissue malformations Genetic toxicity: These oils have been found to cause mutations. Cancer-causing potential: The general conclusion that can be drawn from animal testing is that these oils may potentially cause skin cancer; however, they have not been found to be associated with an increase in tumours elsewhere in the body. The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation (C14-16-18)alkylphenol potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; lubricating oils, petroleum The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: C15-30 hydrotreated neutral • The adverse effects of these materials are associated with undesirable components, and (DMSO <3% w/w by IP 346)* & • The levels of the undesirable components are inversely related to the degree of processing lubricating oils, petroleum • Distillate base oils receiving the same degree or extent of processing will have similar toxicities; C20-50, hydrotreated neutral • The potential toxicity of residual base oils is independent of the degree of processing the oil receives. (DMSO <3% w/w by IP 346) & • The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. paraffinic distillate, light, Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon solvent-dewaxed (severe) molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base (DMSO <3% w/w by IP 346) & oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined paraffinic distillate, heavy, and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have solvent-dewaxed (severe) demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative (DMSO <3% w/w by IP 346)* & results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to paraffinic distillate, heavy, their molecular size solvent-dewaxed (severe). Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating (DMSO <3% w/w by IP 346) base oil s mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)* & For highly and severely refined distillate base oils: paraffinic distillate, light, In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The solvent-dewaxed (severe) semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when (DMSO <3% w/w by IP 346) & tested for skin and eye irritation. Testing for sensitisation has been negative. The effects of repeated exposure vary by species; in animals, paraffinic distillate, heavy, effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been solvent-dewaxed (severe) found to cause reproductive toxicity or significant increases in birth defects. They are also not considered to cause cancer, mutations or (DMSO <3% w/w by IP 346)* & chromosome aberrations paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346) paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, heavy, solvent-dewaxed (severe) No significant acute toxicological data identified in literature search. (DMSO <3% w/w by IP 346)* & paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346) & (C14-16-18)alkylphenol paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, heavy. The substance is classified by IARC as Group 3: solvent-dewaxed (severe) NOT classifiable as to its carcinogenicity to humans. (DMSO <3% w/w by IP 346)* & Evidence of carcinogenicity may be inadequate or limited in animal testing. paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346) Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of nparaffins is inversely proportional to the carbon chain length, with little absorption above $\widetilde{\text{C30}}$. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic

paraffinic distillate, heavy,
solvent-dewaxed (severe)
(DMSO <3% w/w by IP 346)* &
paraffinic distillate, heavy,
solvent-dewaxed (severe).
(DMSO <3% w/w by IP 346)

hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The gut cell may play a major role in determining the proportion of hydrocarbon that becomes available to be deposited unchanged in peripheral tissues such as in the body fat stores or the liver.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

— Data either not available or does not fill the criteria for classification

Data available to make classification

Page 10 of 15

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

Version No: 3.3

SECTION 12 Ecological information

12.1. Toxicity

Test Duration (hr) 48h 504h Test Duration (hr) 48h 504h	Species Crustacea Crustacea Species Crustacea Crustacea Crustacea Crustacea Crustacea Species Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea	Not Available	Not Available Source 1 1 Source 1 1 Source 1 1 Source 1 1
48h 504h Test Duration (hr) 48h 504h Test Duration (hr) 48h 504h Test Duration (hr) 72h	Crustacea Crustacea Species Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea Crustacea Algae or other aquatic plants	>1000mg/l >1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l	1 1 Source 1 1 Source 1 1 1 Source 1 1 1 Source 1 1 1 Source
504h Test Duration (hr) 48h 504h Test Duration (hr) 48h 504h Test Duration (hr) 72h	Crustacea Species Crustacea Crustacea Species Crustacea Crustacea Crustacea Algae or other aquatic plants	>1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l	Source 1 Source 1 Source 1 1 Source 1
Test Duration (hr) 48h 504h Test Duration (hr) 48h 504h Test Duration (hr) 72h	Species Crustacea Crustacea Species Crustacea Crustacea Crustacea Algae or other aquatic plants	Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l	Source 1 Source 1 Source 1 1
48h 504h Test Duration (hr) 48h 504h Test Duration (hr) 72h	Crustacea Crustacea Species Crustacea Crustacea Crustacea Algae or other aquatic plants	>1000mg/l >1mg/l Value >1000mg/l >1mg/l Value >1000mg/l >1mg/l	Source 1 Source 1 1 1
Test Duration (hr) 48h 504h Test Duration (hr) 72h	Crustacea Species Crustacea Crustacea Species Algae or other aquatic plants	>1mg/l Value >1000mg/l >1mg/l Value >1000mg/l	Source 1 Source 1
Test Duration (hr) 48h 504h Test Duration (hr) 72h	Species Crustacea Crustacea Species Algae or other aquatic plants	Value >1000mg/l >1mg/l Value >1000mg/l	Source 1 1 Source 1
48h 504h Test Duration (hr) 72h	Crustacea Crustacea Species Algae or other aquatic plants	>1000mg/l >1mg/l Value >1000mg/l	1 Source
504h Test Duration (hr) 72h	Crustacea Species Algae or other aquatic plants	>1mg/l Value >1000mg/l	1 Source
Test Duration (hr) 72h	Species Algae or other aquatic plants	Value >1000mg/l	Source 1
72h	Algae or other aquatic plants	>1000mg/l	1
	<u> </u>	-	
48h	Crustacea	>1000mg/l	
			1
504h	Crustacea	>1mg/l	1
96h	Algae or other aquatic plants	>1000mg/l	1
Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available
Test Duration (hr)	Species	Value	Source
48h	Crustacea	>100mg/l	2
24h	Crustacea	>100mg/l	2
	Test Duration (hr) 48h	Test Duration (hr) 48h Crustacea 24h Crustacea	Test Duration (hr) Species Value 48h Crustacea >100mg/l

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	P	В	Т	
Relevant available data Not Available Not Available Not Available				vailable
PBT X X				
vPvB	×			
PBT Criteria fulfilled?				No
vPvB				No

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

Version No: 3.3

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- ▶ Recycling
- Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Waste treatment options
Sewage disposal options

Not Available

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number or ID number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard	Class	Not Applic	licable
class(es)	Subsidiary Hazard	Not Applic	licable
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	Hazard identification	(Kemler)	Not Applicable
14.6. Special precautions for	Classification code		Not Applicable
	Hazard Label		Not Applicable
user	Special provisions		Not Applicable
	Limited quantity		Not Applicable
	Tunnel Restriction C	ode	Not Applicable

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
	ICAO/IATA Class	Not Applicable	
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
0.000(00)	ERG Code	Not Applicable	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Special provisions Not Applicable		Not Applicable

Part Number: **47024**, **47025**, **47026**, **47027** Version No: **3.3**

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Print Date: 22/07/2024

Cargo Only Packing Instructions	Not Applicable
Cargo Only Maximum Qty / Pack	Not Applicable
Passenger and Cargo Packing Instructions	Not Applicable
Passenger and Cargo Maximum Qty / Pack	Not Applicable
Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subsidiary Hazard Not Applicable		
14.4. Packing group	Not Applicable		
14.5 Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS Number Not Applicable Special provisions Not Applicable Limited Quantities Not Applicable		

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.2		Not Applicable		
	2. UN proper shipping name	Not Applicable		
14.3	3. Transport hazard class(es)	Not Applicable Not Applicable		
14.4	Packing group	Not Applicable		
14.5	5. Environmental hazard	Not Applicable		
		Classification code	Not Applicable	
1/16	S Special procautions for	Special provisions	Not Applicable	
14.0	user	Limited quantity	Not Applicable	
		Equipment required	Not Applicable	
		Fire cones number	Not Applicable	
14.6	6. Special precautions for user	Special provisions Limited quantity Equipment required	Not Applicable Not Applicable Not Applicable	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
lubricating oils, petroleum C15- 30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	Not Available
lubricating oils, petroleum C20- 50, hydrotreated neutral (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	Not Available
(C14-16-18)alkylphenol	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
lubricating oils, petroleum C15- 30 hydrotreated neutral (DMSO <3% w/w by IP 346)*	Not Available
lubricating oils, petroleum C20- 50, hydrotreated neutral	Not Available

Version No: 3.3

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: **22/07/2024**Print Date: **22/07/2024**

Product name	Ship Type
(DMSO <3% w/w by IP 346)	
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)*	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)	Not Available
(C14-16-18)alkylphenol	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)* is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)* is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

(C14-16-18)alkylphenol is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Additional Regulatory Information

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non- Industrial Use	No ((C14-16-18)alkylphenol)		
Canada - DSL	No ((C14-16-18)alkylphenol)		
Canada - NDSL	No (lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)*; lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346); paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346)*; paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346); (C14-16-18)alkylphenol)		
China - IECSC	No ((C14-16-18)alkylphenol)		
Europe - EINEC / ELINCS / NLP	No ((C14-16-18)alkylphenol)		
Japan - ENCS	Yes		
Korea - KECI	No ((C14-16-18)alkylphenol)		

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

Issue Date: 22/07/2024 Print Date: 22/07/2024

National Inventory	Status		
New Zealand - NZIoC	No ((C14-16-18)alkylphenol)		
Philippines - PICCS	No ((C14-16-18)alkylphenol)		
USA - TSCA	No ((C14-16-18)alkylphenol)		
Taiwan - TCSI	No ((C14-16-18)alkylphenol)		
Mexico - INSQ	No (lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346); paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, heavy, solvent-dewaxed (severe). (DMSO <3% w/w by IP 346); (C14-16-18)alkylphenol)		
Vietnam - NCI	Yes		
Russia - FBEPH	No (lubricating oils, petroleum C15-30 hydrotreated neutral (DMSO <3% w/w by IP 346)*; lubricating oils, petroleum C20-50, hydrotreated neutral (DMSO <3% w/w by IP 346); paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346); (C14-16-18)alkylphenol)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	22/07/2024
Initial Date	03/04/2024

Full text Risk and Hazard codes

H304	May be fatal if swallowed and enters airways.	
H317	May cause an allergic skin reaction.	
H373	H373 May cause damage to organs through prolonged or repeated exposure.	

SDS Version Summary

Version	Date of Update	Sections Updated
2.3	22/07/2024	Toxicological information - Acute Health (skin), Physical and chemical properties - Appearance, Toxicological information - Chronic Health, Hazards identification - Classification, Ecological Information - Environmental, Firefighting measures - Fire Fighter (fire/explosion hazard), Handling and storage - Handling Procedure, Composition / information on ingredients - Ingredients, Stability and reactivity - Instability Condition, Exposure controls / personal protection - Personal Protection (other), Exposure controls / personal protection - Personal Protection (hands/feet), Handling and storage - Storage (storage incompatibility)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ► ENCS: Existing and New Chemical Substances Inventory

Part Number: 47024, 47025, 47026, 47027 Page **15** of **15** Issue Date: 22/07/2024 Version No: 3.3 Print Date: 22/07/2024

Lucas Oil Synthetic 5W-30 C3 ECO Engine Oil

- KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
 TSCS: Trivon Chemical Substances Inventory
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
, EUH208	Expert judgement
, EUH210	Calculation method

Powered by AuthorITe, from Chemwatch.