

Lucas Oil Synthetic 5W-40 C3 Engine Oil Lucas Oil Products UK (GB)

Part Number: 47044, 47045, 47046, 47047

Version No: 1.1

Safety data sheet according to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Issue Date: **16/04/2024** Print Date: **17/04/2024** S.REACH.GB.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	Lucas Oil Synthetic 5W-40 C3 Engine Oil	
Chemical Name	Not Applicable	
Synonyms	Mixture	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Category Consumer	PC24 Lubricants, greases, release products	
Relevant identified uses	Use according to manufacturer's directions.	
Uses advised against	No specific uses advised against are identified.	

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lucas Oil Products UK (GB)	Lucas Oil Products Europe Ltd
Address	Unit 4 Cunliffe Drive Llangefni Industrial Estate LL77 7JA Llangefni Great Britain	Block 3 Harcourt Centre Dublin 2 Ireland
Telephone	+44 (0) 1248 723 666	+44 344 225 5400
Fax	Not Available	Not Available
Website	www.lucasoil.co.uk	www.lucasoil.eu.com
Email	Info@LucasOil.co.uk	info@lucasoil.eu.com

1.4. Emergency telephone number

Association / Organisation	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	ChemTel	
Emergency telephone numbers	020 7188 7188	1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)	
Other emergency telephone numbers	Not Available	+1-813-248-0585 (International)	

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classified according to GB- CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 [1]	Not Applicable

2.2. Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Supplementary statement(s)

EUH208 Contains maleic anhydride. May produce an allergic reaction.

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Part Number: 47044, 47045, 47046, 47047 Issue Date: 16/04/2024 Page 2 of 14 Version No: 1.1 Print Date: 17/04/2024

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

Material contains paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346), paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346), paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346), paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346).

2.3. Other hazards

paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply) Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)	
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)		
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)	
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)	
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Determined to have endocrine-disrupting properties according to Europe Regulation (EU) 528/2012, Europe Regulation (EU) 2017/2100, and Europe Regulation (EU) 2018/605	

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	SCL / M- Factor	Nanoform Particle Characteristics
1. 64742-54-7.* 2.265-157-1 3.649-467-00-8 4.Not Available	0-75	paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Aspiration Hazard Category 1; H304 ^[1]	Not Available	Not Available
1. 64742-55-8.* 2.265-158-7 3.649-468-00-3 4.Not Available	0-75	paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Aspiration Hazard Category 1; H304 ^[1]	Not Available	Not Available
1. 64742-56-9.* 2.265-159-2 3.649-469-00-9 4.Not Available	0-75	paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Aspiration Hazard Category 1; H304 ^[1]	Not Available	Not Available
1. 64742-65-0.* 2.265-169-7 3.649-474-00-6 4.Not Available	0-75	paraffinic distillate, heavy, solvent- dewaxed (severe) (DMSO <3% w/w by IP 346) [e]	Aspiration Hazard Category 1; H304 ^[1]	Not Available	Not Available
1. 108-31-6 2.203-571-6 3.607-096-00-9 4.Not Available	<0.001	maleic anhydride	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1B, Sensitisation (Skin) Category 1A, Serious Eye Damage/Eye Irritation Category 1, Sensitisation (Respiratory) Category 1, Specific Target Organ Toxicity - Repeated Exposure Category 1; H302, H314, H317, H318, H334, H372 [2]	Skin Sens. 1A; H317: C ≥ 0,001 %	Not Available
Legel			H334, H372 ^[2] fication drawn from GB-CLP Regulation, UK SI 2019/720 and UI Substance identified as having endocrine disrupting properties	K SI 2020/1567; 3	3. Classification dra

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.

Page 3 of 14

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

	Fire Incompatibility	None known.		
	5.3. Advice for firefighters			
Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.		 Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. 		
	Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes. May emit acrid smoke. Mists containing combustible materials may be explosive. 		

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by all means available, spillage from entering drains or water courses. Consider evacuation (or protect in place). No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Contain or absorb spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Version No: 1.1

Page 4 of 14

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

▶ Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. Safe handling When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. Fire and explosion protection See section 5 ▶ Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Other information Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known
Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

Protect containers against physical damage and check regularly for leaks.

Observe manufacturer's storage and handling recommendations contained within this SDS.

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Dermal 0.97 mg/kg bw/day (Systemic, Chronic) Inhalation 2.73 mg/m³ (Systemic, Chronic) Inhalation 5.58 mg/m³ (Local, Chronic) Oral 0.74 mg/kg bw/day (Systemic, Chronic) * Inhalation 1.19 mg/m³ (Local, Chronic) *	9.33 mg/kg food (Oral)
maleic anhydride	Dermal 0.2 mg/kg bw/day (Systemic, Chronic) Inhalation 0.081 mg/m³ (Systemic, Chronic) Inhalation 0.081 mg/m³ (Local, Chronic) Dermal 0.2 mg/kg bw/day (Systemic, Acute) Inhalation 0.2 mg/m³ (Systemic, Acute) Inhalation 0.2 mg/m³ (Local, Acute)	0.038 mg/L (Water (Fresh)) 0.379 mg/L (Water - Intermittent release) 0.004 mg/L (Water (Marine)) 0.06 mg/kg sediment dw (Sediment (Fresh Water)) 0.006 mg/kg sediment dw (Sediment (Marine)) 0.01 mg/kg soil dw (Soil)

Page 5 of 14

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
	Dermal 0.1 mg/kg bw/day (Systemic, Chronic) * Inhalation 0.05 mg/m³ (Systemic, Chronic) * Oral 0.06 mg/kg bw/day (Systemic, Chronic) * Inhalation 0.08 mg/m³ (Local, Chronic) * Dermal 0.1 mg/kg bw/day (Systemic, Acute) * Inhalation 0.25 (Systemic, Acute) * Oral 0.1 mg/kg bw/day (Systemic, Acute) *	4.46 mg/L (STP) 6.67 mg/kg food (Oral)

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs).	maleic anhydride	Maleic anhydride	1 mg/m3	3 mg/m3	Not Available	Sen

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	140 mg/m3	1,500 mg/m3	8,900 mg/m3
maleic anhydride	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	2,500 mg/m3	Not Available
maleic anhydride	10 mg/m3	Not Available

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

- Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.
 - Work should be undertaken in an isolated system such as a "glove-box". Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.
 - Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.
 - Open-vessel systems are prohibited.
 - ► Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.
 - Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.
 - For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
 - Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).
 - ▶ Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.
 - Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

8.2.1. Appropriate engineering controls

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: 16/04/2024 Print Date: 17/04/2024

8.2.2. Individual protection measures, such as personal protective equipment







Eve and face protection

- "Safety glasses with side shields
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]"

Skin protection

See Hand protection below

▶ Wear general protective gloves, eg. light weight rubber gloves.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact
- · chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use
- · Contaminated gloves should be replaced.
- As defined in ASTM F-739-96 in any application, gloves are rated as:
- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended

Body protection

Other protection

Hands/feet protection

See Other protection below

- Femployees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filtertype respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]
- ▶ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.
- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.
- Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.

No special equipment needed when handling small quantities

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Version No: 1.1

Issue Date: **16/04/2024**Print Date: **17/04/2024**

Appearance	Amber Clear and Bright Oil		
Physical state	Liquid	Relative density (Water = 1)	0.853
Physical state	Liquid	Relative density (water = 1)	0.853
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-39	Viscosity (cSt)	78.4 @ 40°C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	220	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Inhaled		tion of the respiratory tract (as classified by EC Directives using animal be kept to a minimum and that suitable control measures be used in an		
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.			
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.			
Eye		Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).		
Chronic	There is sufficient evidence to suggest that this material directly caus Oil may contact the skin or be inhaled. Extended exposure can lead warts on the soles of the feet.	ses cancer in humans. to eczema, inflammation of hair follicles, pigmentation of the face and		
Lucas Oil Synthetic 5W-40 C3	тохісіту	IRRITATION		
Engine Oil	Not Available	Not Available		
novoffinio distillato hossa	тохісіту	IRRITATION		
paraffinic distillate, heavy, hydrotreated (severe) (DMSO	Dermal (rabbit) LD50: >5000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		
<3% w/w by IP 346)	Oral (Rat) LD50: >15000 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]		
paraffinic distillate, light, hydrotreated (severe) (DMSO	TOXICITY	IRRITATION		
<3% w/w by IP 346)	Oral (Rat) LD50: >5000 mg/kg * ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		

Page 8 of 14

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: 16/04/2024 Print Date: 17/04/2024

		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
paraffinic distillate, light,	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Inhalation (Rat) LC50: 2.18 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >5000 mg/kg ^[2]	
	TOXICITY	IRRITATION
paraffinic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Inhalation (Rat) LC50: 2.18 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >5000 mg/kg ^[2]	
	TOXICITY	IRRITATION
malaia anhudrida	Dermal (rabbit) LD50: 2620 mg/kg ^[2]	Eye (rabbit): 1% - SEVERE
maleic anhydride	Inhalation (Rat) LC50: >1.088 mg/l4h ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 400 mg/kg ^[2]	Skin: adverse effect observed (corrosive) ^[1]
Legend:	Value obtained from Europe ECHA Registered Substances - Acute specified data extracted from RTECS - Register of Toxic Effect of chells.	toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise mical Substances
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	* Q8 MSDS	
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Animal studies indicate that normal, branched and cyclic paraffins are paraffins is inversely proportional to the carbon chain length, with little to be present in mineral oil, n-paraffins may be absorbed to a greater of the major classes of hydrocarbons are well absorbed into the gastroir hydrocarbons are ingested in association with fats in the diet. Some hy the gut lymph, but most hydrocarbons partly separate from fats and ur determining the proportion of hydrocarbon that becomes available to be stores or the liver.	absorption above C30. With respect to the carbon chain lengths likely extent than iso- or cyclo-paraffins. Intestinal tract in various species. In many cases, the hydrophobic sydrocarbons may appear unchanged as in the lipoprotein particles in indergo metabolism in the gut cell. The gut cell may play a major role in
MALEIC ANHYDRIDE	of persistent asthma-like symptoms within minutes to hours of a docur include a reversible airflow pattern on lung function tests, moderate to and the lack of minimal lymphocytic inflammation, without eosinophilia disorder with rates related to the concentration of and duration of expc is a disorder that occurs as a result of exposure due to high concentra reversible after exposure ceases. The disorder is characterized by diff	re rarely as urticaria or Quincke's oedema. The pathogenesis of ction of the delayed type. Other allergic skin reactions, e.g. contact the of the contact allergen is not simply determined by its sensitisation intact with it are equally important. A weakly sensitising substance with stronger sensitising potential with which few individuals come into any produce an allergic test reaction in more than 1% of the persons exactions between IgE antibodies and allergens and occur rapidly. The the severity of symptoms. Some people may be genetically more potoms. Allergy causing activity is due to interactions with proteins. The discreptibility to nasal inflammation, asthma and eczema. It immune-complexes of the IgG type; cell-mediated reactions (The onset up to four hours following exposure. Exposure to the material ends. This may be due to a non-allergic hich can occur after exposure to high levels of highly irritating previous airways disease in a non-atopic individual, with sudden onset mented exposure to the irritant. Other criteria for diagnosis of RADS severe bronchial hyperreactivity on methacholine challenge testing, and RADS (or asthma) following an irritating inhalation is an infrequent obsure to the irritating substance. On the other hand, industrial bronchitis tions of irritating, cough and mucus production.
Lucas Oil Synthetic 5W-40 C3 Engine Oil & paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	The materials included in the Lubricating Base Oils category are related. The potential toxicity of a specific distillate base oil is inversely related. The adverse effects of these materials are associated with undesirated. The levels of the undesirable components are inversely related to the Distillate base oils receiving the same degree or extent of processing. The potential toxicity of residual base oils is independent of the degree. The reproductive and developmental toxicity of the distillate base oils Unrefined & mildly refined distillate base oils contain the highest levels molecules and have shown the highest potential cancer-causing and roils are produced from unrefined and mildly refined oils by removing o and mildly refined base oils, the highly and severely refined distillate be demonstrated very low mammalian toxicity. Testing of residual oils for results, supporting the belief that these materials lack biologically active their molecular size. Toxicity testing has consistently shown that lubricating base oils have base oil s mutagenic and carcinogenic potential correlates with its 3-7 DMSO extractables (e.g., IP346 assay), both characteristics that are discovered in the properties of the properties of the area.	to the severity or extent of processing the oil has undergone, since: ole components, and a degree of processing; givill have similar toxicities; ee of processing the oil receives. It is inversely related to the degree of processing. It is inversely related to the degree of processing. It is inversely related to the degree of processing. It is inversely related to the degree of processing. It is inversely related to the degree of processing. It is inversely refined distillate base of undesirable components. In comparison to unrefined asse oils have a smaller range of hydrocarbon molecules and have mutation-causing and cancer-causing potential has shown negative and the components of the components are largely non-bioavailable due to low acute toxicities. Numerous tests have shown that a lubricating ring polycyclic aromatic compound (PAC) content, and the level of
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, light,	For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weig semilethal concentration for inhalation is 2.18 to >4 mg/L. The materia tested for skin and eye irritation. Testing for sensitisation has been neg	tht and the semilethal dose by skin contact is >2g/kg body weight. The lis have varied from "non-irritating" to "moderately irritating" when

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

hydrotreated (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)

effects to the testes and lung have been observed, as well as the formation of granulomas. In animals, these substances have not been found to cause reproductive toxicity or significant increases in birth defects. They are also not considered to cause cancer, mutations or chromosome aberrations.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) & paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)

No significant acute toxicological data identified in literature search.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

– Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

Many chemicals may mimic or interfere with the body s hormones, known as the endocrine system. Endocrine disruptors are chemicals that can interfere with endocrine (or hormonal) systems.

Endocrine disruptors interfere with the synthesis, secretion, transport, binding, action, or elimination of natural hormones in the body. Any system in the body controlled by hormones can be derailed by hormone disruptors. Specifically, endocrine disruptors may be associated with the development of learning disabilities, deformations of the body various cancers and sexual development problems.

Endocrine disrupting chemicals cause adverse effects in animals. But limited scientific information exists on potential health problems in humans. Because people are typically exposed to multiple endocrine disruptors at the same time, assessing public health effects is difficult.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

Lucas Oil Synthetic 5W-40 C3	Endpoint	Test Duration (hr)	Species	Value	Source
Engine Oil	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
paraffinic distillate, heavy,	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
hydrotreated (severe) (DMSO	NOEC(ECx)	504h	Crustacea	>1mg/l	1
<3% w/w by IP 346)	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
paraffinic distillate, light,	Endpoint	Test Duration (hr)	Species	Value	Source
nydrotreated (severe) (DMSO	NOEC(ECx)	504h	Crustacea	>1mg/l	1
<3% w/w by IP 346)	EC50	48h	Crustacea	>1000mg/l	1
paraffinic distillate, light,	Endpoint	Test Duration (hr)	Species	Value	Source
solvent-dewaxed (severe)	NOEC(ECx)	504h	Crustacea	>1mg/l	1
(DMSO <3% w/w by IP 346)	EC50	48h	Crustacea	>1000mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
paraffinic distillate, heavy,	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
solvent-dewaxed (severe)	NOEC(ECx)	504h	Crustacea	>1mg/l	1
(DMSO <3% w/w by IP 346)	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
maleic anhydride	Endpoint	Test Duration (hr)	Species	Value	Source
	ErC50	72h	Algae or other aquatic plants	29mg/l	1

Page 10 of 14

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: 16/04/2024 Print Date: 17/04/2024

EC50	72h	Algae or other aquatic plants	29mg/l	1
LC50	96h	Fish	75mg/l	2
EC50	48h	Crustacea	42.81mg/l	2
NOEC(ECx)	504h	Crustacea	10mg/l	1

Leaend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
maleic anhydride	HIGH	HIGH

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
maleic anhydride	LOW (LogKOW = 1.6187)

12.4. Mobility in soil

Ingredient	Mobility
maleic anhydride	HIGH (Log KOC = 1)

12.5. Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT	X	×	×
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

12.6. Endocrine disrupting properties

The evidence linking adverse effects to endocrine disruptors is more compelling in the environment than it is in humans. Endocrine distruptors profoundly alter reproductive physiology of ecosystems and ultimately impact entire populations. Some endocrine-disrupting chemicals are slow to break-down in the environment. That characteristic makes them potentially hazardous over long periods of time. Some well established adverse effects of endocrine disruptors in various wildlife species include; eggshell-thinning, displayed of characteristics of the opposite sex and impaired reproductive development. Other adverse changes in wildlife species that have been suggested, but not proven include; reproductive abnormalities, immune dysfunction and skeletal deformaties.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty
- Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.

	 Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available
Sewage disposal options	Not Available

Page **11** of **14**

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: 16/04/2024 Print Date: 17/04/2024

SECTION 14 Transport information

Labels Required

Version No: 1.1

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS		
14.1. UN number or ID number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)		ot Applicable ot Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
	Hazard identification (Ker	mler) Not Applicable
	Classification code	Not Applicable
14.6. Special precautions for	Hazard Label	Not Applicable
user	Special provisions	Not Applicable
	Limited quantity	Not Applicable
	Tunnel Restriction Code	Not Applicable

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable			
14.2. UN proper shipping name	Not Applicable			
	ICAO/IATA Class	Not Applicable		
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
Class(ss)	ERG Code	Not Applicable		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		Not Applicable	
	Cargo Only Maximum Qty / Pack		Not Applicable	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		Not Applicable	
	Passenger and Cargo Maximum Qty / Pack		Not Applicable	
	Passenger and Cargo Limited Quantity Packing Instructions		Not Applicable	
	Passenger and Cargo Limited Ma	aximum Qtv / Pack	Not Applicable	

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subsidiary Hazard Not Applicable	
14.4. Packing group	Not Applicable	
14.5 Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number Not Applicable Special provisions Not Applicable Limited Quantities Not Applicable	

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable
14.2. UN proper shipping name	Not Applicable

Page 12 of 14

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

	_		
14.3. Transport hazard class(es)	Not Applicable Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	Classification code	Not Applicable	
	Special provisions	Not Applicable	
14.6. Special precautions for user	Limited quantity	Not Applicable	
	Equipment required	Not Applicable	
	Fire cones number	Not Applicable	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Version No: 1.1

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
maleic anhydride	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346)	Not Available
maleic anhydride	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Great Britain GB mandatory classification and labelling list (GB MCL) $\,$

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Page 13 of 14

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

Great Britain GB mandatory classification and labelling list (GB MCL)

UK Workplace Exposure Limits (WELs).

Additional Regulatory Information

Not Applicable

Version No: 1.1

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (paraffinic distillate, heavy, hydrotreated (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, heavy, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346); maleic anhydride)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (paraffinic distillate, light, hydrotreated (severe) (DMSO <3% w/w by IP 346); paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346))
Vietnam - NCI	Yes
Russia - FBEPH	No (paraffinic distillate, light, solvent-dewaxed (severe) (DMSO <3% w/w by IP 346))
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	16/04/2024
Initial Date	17/04/2024

Full text Risk and Hazard codes

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit

Page 14 of 14

Version No: 1.1

Lucas Oil Synthetic 5W-40 C3 Engine Oil

Issue Date: **16/04/2024**Print Date: **17/04/2024**

- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ► NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
, EUH208	Expert judgement

Powered by AuthorITe, from Chemwatch.