Lucas Oil Synthetic 5W-40 A3/B4 Engine Oil

Lucas Oil Synthetic 5W-40 A3/B4 Engine Oil is a fully synthetic engine oil, formulated from the finest quality synthetic base oils and enriched with premium performance additives that guarantee exceptional protection and efficiency.

Designed to meet and exceed the stringent specifications set by leading automotive manufacturers, this engine oil ensures seamless operation, reduces friction, and enhances fuel efficiency.

For use in Renault and Volkswagen vehicles, as well as other petrol and diesel engines, that demand the superior properties of an SAE 5W-40 of this specification.

FEATURES AND BENEFITS:

- Superior engine-wide wear protection
- Outstanding control over piston deposits
- Reliable defence against sludge formation

MAIN APPLICATIONS:

For use in petrol, LPG, and diesel engines, including turbo and direct injection types. Ideal for high-performance, multi-valve engines with catalysts.

Meets ACEA A3/B4.

SPECIFICATIONS:

Meets the requirements of:

- ACEA A3/B4
- API CF / SN
- PSA B71 2296
- Renault RN 0700 / 0710
- Ford M2C917-A
- VAG VW 502.00 / 505.00 / 505.01
- GM LL-B-025
- MB 229.3
- Volvo VCC 95200356

INSERT IMAGE HERE

PART NUMBER AND SIZE:

47040-1 Litre (Case of 12).

47041 - 5 Litre (Case of 4).

47042 - 20 Litre (1 Drum).

47043 – 204 Litre (1 Drum).

TYPICAL PHYSICAL CHARACTERISTICS:

PROPERTIES	Method	Unit	Typical
Density, 15°c	D 4052	g/ml	0.853
Kinematic Viscosity, 40°c (extrapolated)	D 445	mm²/s	89.2
Kinematic Viscosity, 100°c	D 445	mm²/s	14.3
Viscosity Index	D 2270	-	168
Apparent Viscosity, -30 °C	D 5293	mPa.s	6200
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5
Flash Point, COC	D 92	°C	240

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

LINKS AND ADDITIONAL INFORMATION:

For additional product or health and safety information, including product Safety Data Sheets, visit <u>LucasOil.co.uk</u>